



HPE Aruba Instant On 1430 24G Switch



Model: R8R49A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017537962

Product Code: 203216

R5,001

The HPE Networking Instant On 1430 24G Switch is designed to meet the demands of businesses, offering a blend of performance, reliability, and networking features. With 24 RJ-45 connectors supporting 10/100/1000 Base-T interfaces, this switch provides flexible connectivity options to accommodate a variety of devices and network configurations. Its performance is highlighted by a throughput of 35.71 Mpps and a switching capacity of 48 Gbps, ensuring efficient data traffic management even during peak times.

The switch's fanless design not only allows for silent operation but also contributes to its durability, with an impressive MTBF of 199.5 years. It supports essential networking features such as DiffServ Code Point (DSCP) support, Spanning Tree Protocol (STP), and VoIP support, facilitating effective network management and prioritization of data traffic. Additionally, its ability to operate in a wide range of environmental conditions without compromising performance makes it a versatile choice for any business setting. Whether for a small office or a large enterprise, the HPE Networking Instant On 1430 24G Switch is engineered to provide a reliable, high-performance networking solution.

Product Description: HPE Networking Instant On 1430 24G Switch - switch - 24 ports - unmanaged - rack-mountable | Device Type: Switch - 24 ports - unmanaged | Enclosure Type: Rack-mountable 1U

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

| Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 | Performance: Throughput: 35.71 Mpps
Switching capacity: 48 Gbps Latency (100 Mbps): 2.7 µs Latency (1 Gbps): 1.8 µs | Capacity: MAC
address entries: 8192 | MAC Address Table Size: 8192 entries | Jumbo Frame Support: 9216 bytes |
Features: 2MB packet buffer, fanless, wall mountable, DSCP support, VoIP support, MDI/MDI-X switch,
flow control, auto-sensing per device, STP support | Compliant Standards: IEEE 802.3, IEEE 802.3u,
IEEE 802.3ab, IEEE 802.1p, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z, IEEE 802.3i | Power: AC 100-240
V (50/60 Hz) 2 A | Dimensions (WxDxH): 34 cm x 22.5 cm x 4.4 cm | Weight: 1.91 kg | Pricing Type:
BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950