

HPE Aruba Instant On 1430 26G 2SFP Switch



Model: R8R50A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017537979

Product Code: 203217

R6,201

The HPE Networking Instant On 1430 26G 2SFP Switch is a versatile and efficient solution designed to meet the networking needs of modern businesses. With 26 RJ-45 ports for 10/100/1000 Base-T connections and 2 SFP ports for 100/1000 connectivity, this switch offers flexible and high-speed network connections. Engineered for efficient performance, it has a 56 Gbps switching capacity and 41.68 Mpps throughput, ensuring efficient data handling for business operations. The switch operates reliably across a wide range of environmental conditions, thanks to its robust design that can withstand diverse temperatures and humidity levels. Compliance with a broad array of standards, including IEEE 802.3 and IEEE 802.3ab, ensures dependable connectivity and adherence to regulatory requirements. Furthermore, its impressive MTBF of 171.9 years signifies reliability and reduced maintenance costs. The fanless design not only ensures silent operation but also contributes to its energy efficiency, with a standby power consumption of only 8 W, making it an economical choice for any network infrastructure.

Product Description: HPE Networking Instant On 1430 26G 2SFP Switch - switch - 26 ports - unmanaged - rack-mountable | Device Type: Switch - 26 ports - unmanaged | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 26 x 10/100/1000 + 2 x 100/1000 SFP |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Performance: Throughput: 41.68 Mpps Switching capacity: 56 Gbps Latency (100 Mbps): 5.2 μ s
Latency (1 Gbps): 2.9 μ s | Capacity: MAC address entries: 16384 | MAC Address Table Size: 16384
entries | Jumbo Frame Support: 9216 bytes | Features: 12MB packet buffer, fanless, wall mountable,
DSCP support, VoIP support, MDI/MDI-X switch, flow control, auto-sensing per device, STP support |
Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3az, IEEE
802.3x, IEEE 802.3z, IEEE 802.3i | Power: AC 100-240 V (50/60 Hz) 0.4 A | Dimensions (WxDxH): 38.8
cm x 22.5 cm x 4.4 cm | Weight: 2.27 kg | Pricing Type: BTO | Manufacturer Warranty: Limited
lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950