

HPE Aruba IOn 1430 8G Switch



Model: R8R45A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017601571

Product Code: 203219

R1,944

The HPE Networking Instant On 1430 8G Switch is designed to meet the demands of modern businesses, offering a blend of performance, reliability, and energy efficiency. This switch features 8 Gigabit Ethernet ports that provide high-speed connectivity and support for a wide range of network configurations. With a robust switching capacity of 16 Gbps and support for up to 8192 MAC address entries, it can handle significant data traffic, making it an ideal choice for small to medium-sized business networks. Advanced networking features such as VoIP support, DiffServ Code Point (DSCP) support, and Spanning Tree Protocol (STP) support enhance its functionality, while the fanless design ensures silent operation, perfect for noise-sensitive environments. The switch's compliance with a broad array of safety and environmental standards, along with an impressive MTBF of 416.2 years, underscores its reliability and durability. Furthermore, its energy-efficient design, including support for IEEE 802.3az and low power consumption in standby mode, makes it an environmentally friendly choice, reducing operational costs.

Product Description: HPE Networking Instant On 1430 8G Switch - switch - 8 ports - unmanaged |

Device Type: Switch - 8 ports - unmanaged | Subtype: Gigabit Ethernet | Ports: 8 x 10/100/1000 |

Performance: Throughput: 11.9 Mbps Switching capacity: 16 Gbps Latency (100 Mbps): 2.7 µs

Latency (1 Gbps): 1.8 µs | Capacity: MAC address entries: 8192 | MAC Address Table Size: 8192

entries | Jumbo Frame Support: 9216 bytes | Features: 2MB packet buffer, fanless, wall mountable,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

DSCP support, VoIP support, MDI/MDI-X switch, flow control, auto-sensing per device, STP support | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z, IEEE 802.3i | Power: AC 100-240 V (50/60 Hz) 1 A | Dimensions (WxDxH): 15.7 cm x 13.8 cm x 3.7 cm | Weight: 590 g | Localisation: English / Europe | Pricing Type: BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950