



HPE Aruba IOn 1430 16G Switch



Model: R8R47A#ABB

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017601984

Product Code: 203220

R4,213

The HPE Networking Instant On 1430 16G Switch is designed to meet the demands of modern businesses, offering a blend of performance, reliability, and eco-friendly operation. This switch provides 16 RJ-45 connectors for 10/100/1000 Base-T interfaces, accommodating a wide range of networking needs with high-speed connectivity. With a throughput of 23.8 Mpps and a switching capacity of 32 Gbps, it handles substantial data traffic, ensuring smooth and reliable network performance.

Advanced features such as 2MB packet buffer, DiffServ Code Point (DSCP) support, and Spanning Tree Protocol (STP) support, enhance the efficiency and reliability of the network, making it well-suited for supporting VoIP and other critical applications. The switch's design prioritizes longevity and reliability, with a mean time between failures (MTBF) of 269.8 years, providing a dependable solution for your networking infrastructure. Additionally, its fanless design not only ensures silent operation but also contributes to reduced energy consumption, highlighting the switch's eco-friendly approach to networking.

Product Description: HPE Networking Instant On 1430 16G Switch - switch - 16 ports - unmanaged - rack-mountable | Device Type: Switch - 16 ports - unmanaged | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 16 x 10/100/1000 | Performance: Throughput: 23.8 Mpps

Switching capacity: 32 Gbps Latency (100 Mbps): 2.7 µs Latency (1 Gbps): 1.8 µs | Capacity: MAC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

address entries: 8192 | MAC Address Table Size: 8192 entries | Jumbo Frame Support: 9216 bytes |
Features: 2MB packet buffer, fanless, wall mountable, DSCP support, VoIP support, MDI/MDI-X switch,
flow control, auto-sensing per device, STP support | Compliant Standards: IEEE 802.3, IEEE 802.3u,
IEEE 802.3ab, IEEE 802.1p, IEEE 802.3az, IEEE 802.3x, IEEE 802.3z, IEEE 802.3i | Power: AC 100-240
V (50/60 Hz) 0.2 A | Dimensions (WxDxH): 27.5 cm x 25.8 cm x 4.4 cm | Weight: 1.72 kg |
Localisation: English / Europe | Pricing Type: BTO | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950