TRENDNET 10-Port Gigabit Web Smart PoE+ Switch

Model: TPE-1021WS

Manufacturer: TRENDNET

EAN: 710931162103

Product Code: 203242

R6,707

TRENDnet's Gigabit Web Smart PoE+ Switch series offers advanced L2+ features with enhanced traffic management controls to meet the evolving demands of SMB networks. This rack mountable IPv6-ready managed switch comes with an intuitive web-based interface. Advanced managed switch features include LACP to increase bandwidth between switches by grouping ports together, VLANs for segmenting and isolating virtual LAN groups, QoS for traffic prioritization, port bandwidth controls, and SNMP monitoring, making this a powerful solution for any SMB network. Improve voice performance by isolating and prioritizing VoIP traffic from normal data traffic with an easy-to-use voice VLAN feature. Easily manage and configure TRENDnet's Web Smart PoE+ Managed Switch Series remotely by updating switches to the firmware for access to TRENDnet Hive.
Product Description: TRENDnet TPE-1021WS - switch - 10 ports - smart - rack-mountable - TAA Compliant | Device Type: Switch - 10 ports - smart | Enclosure Type: Rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 8 x 10/100/1000 (PoE+) + 2 x 10/100/1000/SFP | Power Over Ethernet (PoE): PoE+ | PoE Budget: 130 W | Performance: Switching capacity: 20 Gbps Forwarding rate: 14.9 Mpps | MAC Address Table Size: 8K entries | Jumbo Frame Support: 10000 bytes | Remote

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Management Protocol: SNMP 1, SNMP 2, RMON 1, Telnet, SNMP 3, HTTP, HTTPS, SSH-2 | Features: Layer 3 switching, DHCP support, IGMP snooping, IPv6 support, QoS, MLD snooping, fanless, LACP support, LLDP support, static routing, IGMP support | Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.3x, IEEE 802.3ad (LACP), IEEE 802.1w, IEEE 802.1x, IEEE 802.1s, IEEE 802.1ab (LLDP), IEEE 802.3at, IEEE 802.3az | Power: AC 100-240 V (50/60 Hz) | Dimensions (WxDxH): 33 cm x 18 cm x 4.4 cm | Weight: 1.76 kg | TAA Compliant: Yes | Manufacturer Warranty: 3-year warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950