



HPE Aruba Networking CX 6200F 24G Class-4 PoE 4SFP 370W Switch



Model: S0M82A

Manufacturer: HEWLETT PACKARD ENTERPRISE

EAN: 190017634920

Product Code: 203253

R87,506

The HPE Aruba Networking CX 6200 Switch Series is a next-gen family of stackable access switches ideal for enterprise branch offices, campuses, and SMB networks. With a cloud-centric design that combines a fully programmable OS with the HPE Aruba Network Analytics Engine, the HPE Aruba Networking CX 6200 extends good monitoring and troubleshooting capabilities to the access layer. Support of Aruba NetEdit and the Aruba CX Mobile App verify that configurations are flawless and easy to deploy.

Make your network ready for unpredictable demands with a powerful Aruba Gen7 ASIC architecture to deliver fast, non-blocking performance. Aruba Virtual Stacking Framework (VSF) allows for stacking of 8 switches, providing scale and simplified management.

Product Description: HPE Aruba Networking CX 6200F 24G Class 4 PoE 4SFP 370W Switch - switch -

Max. Stacking Distance 10 kms - 24 ports - Managed - rack-mountable | Device Type: Switch - 24

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ports - L3 - Managed - stackable | Enclosure Type: Front and side to back rack-mountable 1U | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 (PoE+) + 4 x 100/1000 SFP | Power Over Ethernet (PoE): PoE+ | PoE Budget: 370 W | Performance: Switching capacity: 128 Gbps Throughput: 95.2 Mpps Latency (1 Gbps): 2.28 µs Latency (10 Gbps): 1.46 µs Stacking bandwidth: 40 Gbps | Capacity: Packet buffer size: 8 MB IPv4 ACL entries (ingress): 5120 IPv6 ACL entries (ingress): 1280 MAC ACL entries (ingress): 5120 IPv4 ACL entries (egress): 2048 IPv6 ACL entries (egress): 512 MAC ACL entries (egress): 2048 IPv4 host table capacity: 8192 IPv6 host table capacity: 8192 IPv4 routes (Unicast): 2048 IPv6 routes (Unicast): 1024 IGMP groups: 1024 MLD groups: 1024 | MAC Address Table Size: 32768 entries | Jumbo Frame Support: 9220 bytes | Routing Protocol: RIP-2, IGMPv2, IGMP, OSPFv2, IGMPv3, OSPFv3, MLDv2, MLD | Remote Management Protocol: RMON, CLI, MIB | Features: VRRP support, TPM, UDLD, DWRR, CoS, ToS, BPDU, PoE Class 4, RPVST+, LLDP, UTM, EQS, Address Resolution Protocol | Compliant Standards: IEEE 802.3, IEEE 802.1D, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3af, IEEE 802.1w, IEEE 802.1s, IEEE 802.1t, IEEE 802.1v, IEEE 802.1ab (LLDP), IEEE 802.1ak, IEEE 802.3at, IEEE 802.1AX | Power: AC 100-127/200-240 V (50/60 Hz) | Dimensions (WxDxH): 44.25 cm x 30.43 cm x 4.37 cm | Weight: 4.39 kg | System Requirements: AOS-CX | Manufacturer Warranty: Limited lifetime warranty | Designed For: CX 6200F 24G Class4 PoE 4SFP+ 370W Switch

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950