



CISCO Catalyst 1200 24-port GE 4x10G SFP+



Model: C1200-24T-4X

Manufacturer: CISCO

EAN: 889728521734

Product Code: 203268

R7,850

The Cisco Catalyst 1200-24T-4X switch is the next generation of affordable, smart switches that combine powerful network performance, security, and reliability with a comprehensive suite of network features you need for a solid small business network.

Product Description: Cisco Catalyst 1200-24T-4X - switch - 24 ports - smart - rack-mountable | Device Type: Switch - 24 ports - L3 - smart | Enclosure Type: Rack-mountable | Subtype: Gigabit Ethernet | Ports: 24 x 10/100/1000 + 4 x 10Gb Ethernet SFP+ | Performance: Forwarding rate (64-byte packets): 95.23 Mpps Switching capacity: 128 Gbps | Capacity: MSTP instances: 8 PVST+ instances: 126 RPVST+ instances: 126 Link aggregation groups: 4 Link aggregation ports: 8 Active VLANs: 255 IGMP multicast groups: 255 IPv4 routes (static): 32 IPv4 interfaces: 16 ACL rules: 512 Priority queues: 8 Packet buffer size: 1.5 MB | MAC Address Table Size: 8000 entries | Jumbo Frame Support: 9000 bytes | Routing Protocol: STP, static IP routing, MSTP, RSTP, IGMP, IGMPv2, IGMPv3, CIDR, MLD, MLDv2, Bounjour | Remote Management Protocol: CLI, Telnet, SSH, SSH-2, DHCP, ICMP, SNMP, RADIUS, Syslog, HTTP, HTTPS, SNMP 2c, SNMP 3, RMON, TFTP, SCP | Features: Fanless, QoS, ACL support, eco-friendly button, EEE, PVST+, Link Aggregation, port grouping, LACP, LAG, VLAN support, Auto Surveillance VLAN, Guest VLAN, port-based VLAN, tag-based VLANs, VLAN management, Voice

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

VLAN, VSDP, Zero-Touch Deployment, GARP, GVRP, IGMP snooping, IGMP querier, loopback detection, UDP, BOOTP support, STP loop guard, SCT, SSD, trustworthy systems, Port Security, Broadcast Storm Control, Multicast Storm Control, Storm Control, Unknown Storm Control, DoS attack prevention, TCP/UDP proxy, DSCP based CoS, SP, WRR queuing, CoS, ToS, DiffServ support, EQS, ingress rate limiting, TCP congestion, SNTP support, TFTP support, DHCP client, DNS client, SNMP trap, remote firmware upgrade, Cable Diagnostics Function, DHCP server, port mirroring, SCP, VLAN mirroring, Telnet client, cable length detection, chip guard, boot integrity, LLDP, LLDP-MED, CDP, reset button, time-based port operation, IPv4 and IPv6 dual stack, Telnet server, DAD, path MTU discovery, WRR, Unicast Storm Control, DoS protection, HoL Blocking Prevention, DHCP relay, RPVST+, MSTP support, layer 3 routing | Compliant Standards: IEEE 802.1x, IEEE 802.3az, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3ad (LACP), IEEE 802.1Q, IEEE 802.1p, IEEE 802.1ab (LLDP), IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z | Power: AC 100-240 V (50 - 60 Hz) | Dimensions (WxDxH): 44.5 cm x 24 cm x 4.4 cm | Weight: 2.78 kg | Manufacturer Warranty: Limited lifetime warranty

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950