

Asustor AS1102TL NAS/storage server Mini Tower Realtek RTD1619B 1 GB DDR4 0 TB ADM Black



Model: AS1102TL

Manufacturer: ASUSTOR

EAN: 4710474831531

Product Code: 20354

R3,366

Certification: FCC, CE, VCCI, BSMI, C-TICK, KCC, BIS, CCC | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): 0 - 40 °C | RAID support: Yes | Dynamic DNS (DDNS): Yes | Storage drive capacity: 0 GB | Ethernet LAN data rates: 1000 Mbit/s | USB port: Yes | Internal memory type: DDR4 | Ethernet LAN: Yes | Total installed storage capacity: 0 TB | Supported network protocols: CIFS/SMB, SMB 2.0/3.0, AFP, NFS, FTP, TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP, Syslog | S.M.A.R.T. support: Yes | Chassis type: Mini Tower | Noise level: 18.6 dB | Flash memory: 8000 MB | Power consumption (sleep): 3.1 W | Number of fans: 1 fan(s) | Jumbo frames support: Yes |

Storage drive sizes supported: 3.5" | Cooling type: Active | Server operating systems supported:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Windows Server 2012 | Browser supported: Firefox, Chrome, Safari, Microsoft Edge | USB 2.0 ports quantity: 1 | Number of power supply units: 1 | Operating relative humidity (H-H): 5 - 95% | RAID levels: JBOD | RAID levels: 0 | RAID levels: 1 | AC input voltage: 100-240 V | Processor frequency: 1.7 GHz | Processor manufacturer: Realtek | Device class: Small & Medium Business | Power consumption (typical): 11.7 W | Windows operating systems supported: Windows 8 | Height: 165 mm | Product colour: Black | Storage drives installed: No | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows Vista | Operating system installed: ADM | Fan diameter: 7 cm | Operating system version: 4.0 | Number of users: 4096 user(s) | Snapshot: Yes | Weight: 1.14 kg | Backup features: Cloud | Backup function: Yes | Backup features: USB drive | Server operating systems supported: Windows Server 2003 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Server operating systems supported: Windows Server 2016 | Security algorithms: 256-bit AES | Server operating systems supported: Windows Server 2008 | Supported storage drive types: HDD | iSCSI support: Yes | Width: 102 mm | Supported storage drive interfaces: Serial ATA III | Access Control List (ACL): Yes | Windows operating systems supported: Windows XP | Mac operating systems supported: Mac OS X 10.10 Yosemite | Type: NAS | Online RAID expansion: Yes | Wake-on-LAN ready: Yes | Number of storage drives supported: 2 | Processor cores: 4 | Load balancing system: Yes | Depth: 218 mm | Installed storage drive type: No | Windows operating systems supported: Windows 7 | Ethernet LAN data rates: 100 | Internal memory: 1 GB | Online RAID migration: Yes | Processor family: Realtek | Processor model: RTD1619B | Link aggregation: Yes | Power supply unit (PSU) capacity: 65 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950