

Asustor DRIVESTOR 2 Pro Gen2 AS3302T v2 NAS Realtek RTD1619B 2 GB DDR4 ADM Black



Model: AS3302T v2

Manufacturer: ASUSTOR

EAN: 4710474831517

Product Code: 20355

R5,246

Certification: FCC, CE, VCCI, BSMI, C-TICK, KCC, BIS, CCC | Ethernet LAN data rates: 2500 Mbit/s | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 1000 Mbit/s | Wake-on-LAN ready: Yes | RAID support: Yes | Web-based management: Yes | Product colour: Black | Weight: 1.6 kg | Supported storage drive types: HDD & SSD | Supported storage drive interfaces: Serial ATA III | LED indicators: Yes | Security algorithms: SSH | AC input voltage: 100 - 240 V | Security algorithms: SSL/TLS | Security algorithms: 256-bit AES | Security algorithms: HTTPS | Operating system installed: ADM | Mac operating systems supported: Mac OS X 12.0 Monterey | Mac operating systems supported: Mac OS X 10.9 Mavericks | Mac operating systems supported: Mac OS X 10.7 Lion | Mac operating systems supported: Mac OS X 11.0 Big Sur | Share folder access right management: Yes | Width: 114

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mm | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | RAID levels: 5 | Supported file systems: exFAT | Processor family: Realtek | iSCSI support: Yes | Operating relative humidity (H-H): 5 - 95% | RAID levels: 6 | RAID levels: JBOD | Supported file systems: FAT32 | Flash memory: 8192 MB | Mac operating systems supported: Mac OS X 10.8 Mountain Lion | Mac operating systems supported: Mac OS X 10.7.5 Lion | Backup features: Cloud | Processor model: RTD1619B | Noise level (idle): 18.6 dB | Depth: 230 mm | Ethernet LAN: Yes | Windows operating systems supported: Windows XP | Internal memory: 2 GB | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 11 | Windows operating systems supported: Windows 10 | Height: 170 mm | Windows operating systems supported: Windows 7 | Processor cores: 4 | Number of power supply units: 1 | RAID levels: 10 | Supported file systems: ext4 | Number of storage drives supported: 2 | Supported file systems: BTRFS | RAID levels: 0 | Supported file systems: HFS+ | Supported file systems: ext3 | Supported file systems: NTFS | RAID levels: 1 | Server operating systems supported: Windows Server 2012 | Server operating systems supported: Windows Server 2016 | Browser supported: Microsoft Edge, Firefox, Chrome | Operating temperature (T-T): 0 - 40 °C | Power supply location: Built-in | Ethernet LAN (RJ-45) ports: 1 | Internal memory type: DDR4 | Operating system version: 4.1 | Windows operating systems supported: Windows Vista | Cooling type: Active | Linux operating systems supported: Yes | Mac operating systems supported: Mac OS X 10.6 Snow Leopard | Mac operating systems supported: Mac OS X 13.0 Ventura | Server operating systems supported: Windows Server 2022 | Type: NAS | Server operating systems supported: Windows Server 2019 | Server operating systems supported: Windows Server 2008 | Server operating systems supported: Windows Server 2003 | Device class: Home & Home Office | Processor frequency: 1.7 GHz | Access Control List (ACL): Yes | Power supply unit (PSU) capacity: 65 W | Processor manufacturer: Realtek | Storage drive size: 2.5/3.5" | Power consumption (typical): 13.1 W | Hot-swap drive bays: Yes | Number of users: 4096 user(s) | Other operating systems supported: UnixWare | Backup function: Yes | Fan diameter: 7 cm | Other operating systems supported: FreeBSD | Jumbo frames support: Yes | USB port: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950