

Asustor AS1202T NAS/storage server Tower Realtek 1 GB DDR4 0 TB ADM Black



Model: AS1202T

Manufacturer: ASUSTOR

EAN: 4710474831937

Product Code: 20446

R3,849

Online RAID migration: Yes | iSCSI support: Yes | System log: Yes | Bad block scan: Yes | Total installed storage capacity: 0 TB | Operating system version: 5.0 | Access Control List (ACL): Yes | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 11 | Height: 165 mm | Backup function: Yes | Width: 102 mm | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | LED indicators: Yes | Processor frequency: 1.7 GHz | Device class: Home & Home Office | Power consumption (typical): 11.6 W | Processor manufacturer: Realtek | AC input voltage: 100 - 240 V | Storage drives installed: No | Security algorithms: 256-bit AES | Server operating systems supported: Windows Server 2016 | Product colour: Black | Web-based management: Yes | Security algorithms: HTTPS | Server operating systems supported: Windows

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Server 2022 | Storage temperature (T-T): -20 - 70 °C | Ethernet LAN data rates: 2500 Mbit/s | Chassis type: Tower | Ethernet LAN data rates: 100 | Server operating systems supported: Windows Server 2008 R2 | Browser supported: Firefox, Chrome, Safari, Microsoft Edge | Installed storage drive type: No | Operating system installed: ADM | Depth: 218 mm | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN (RJ-45) ports: 1 | RAID support: Yes | Noise level: 18.6 dB | Security algorithms: SNMP | Server operating systems supported: Windows Server 2003 | Storage drive interface: Serial ATA | Supported network protocols: Supported), TFTP, WebDAV, Rsync, SSH, SFTP, iSCSI/IP-SAN, HTTP, HTTPS, Proxy, SNMP, Syslog | S.M.A.R.T. support: Yes | Internal memory: 1 GB | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | Type: NAS | Server operating systems supported: Windows Server 2019 | Internal memory type: DDR4 | USB port: Yes | Storage drive sizes supported: 3.5" | Ethernet LAN: Yes | Number of fans: 1 fan(s) | Jumbo frames support: Yes | Security algorithms: SSH | Server operating systems supported: Windows Server 2012 | Flash memory: 8000 MB | DHCP server: Yes | Supported file systems: exFAT | RAID levels: 1 | Operating relative humidity (H-H): 5 - 95% | Number of storage drives supported: 2 | Processor family: Realtek | RAID levels: 0 | Supported file systems: HFS+ | Linux operating systems supported: Yes | Cooling type: Active | Supported file systems: ext3 | Supported file systems: NTFS | Fan diameter: 7 cm | Weight: 1.14 kg | Snapshot: Yes | Number of users: 4096 user(s) | RAID levels: JBOD | Supported file systems: FAT32 | Supported file systems: ext4 | Power supply unit (PSU) capacity: 65 W | Processor cores: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950