



Supermicro SuperServer 5019P-MTR Intel C622 LGA 3647 (Socket P) Rack (1U) Black

Model: SYS-5019P-MTR

Manufacturer: SUPERMICRO

EAN: 672042263752

Product Code: 325813

R28,857

Bundled software: Intel® Node Manager IPMI 2.0 KVM with dedicated LAN NMI SPM, SUM SuperDoctor® 5 Watch Dog | Operating temperature (T-T): 10 - 35 °C | Supported RDIMM clock speeds: 2400 | Package weight: 13.8 kg | Height: 43 mm | Depth: 503 mm | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Width: 437 mm | Weight: 8 kg | Supported RDIMM clock speeds: 2666 MHz | BIOS memory size: 32 Mbit | Supported memory types: DDR4-SDRAM | PCI Express slots version: 3.0 | LAN controller: Intel® X557 | Ethernet LAN (RJ-45) ports: 2 | Motherboard chipset: Intel C622 | USB 2.0 ports quantity: 2 | Number of redundant power supplies installed: 1 | Number of DIMM slots: 8 | Supported storage drive interfaces: Serial ATA III | Number of processors supported: 1 | Ethernet LAN: Yes | Fan diameter: 4 cm | Ethernet LAN data rates: 10000 Mbit/s | Built-in processor: No | IPMI LAN (RJ-45) port: Yes | Number of fans: 4 fan(s) | Storage drive sizes supported: 3.5" |

Processor socket: LGA 3647 (Socket P) | Harmonized System (HS) code: 84714100 | Maximum

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

RDIMM memory: 256 GB | LAN controller: Intel® X772 | Product colour: Black | Power supply: 400 W | Serial ports quantity: 2 | Supported RDIMM clock speeds: 2133 MHz | BIOS type: AMI | Chassis type: Rack (1U) | Operating relative humidity (H-H): 8 - 90% | Ethernet interface type: 10 Gigabit Ethernet | Storage temperature (T-T): -40 - 70 °C | Number of storage drives supported: 4 | Processor family: Intel® Xeon® | PCI Express x16 slots: 1 | ECC: Yes | Hot-swap HDD bays: Yes | Storage relative humidity (H-H): 5 - 95% | Sustainability certificates: RoHS | VGA (D-Sub) ports quantity: 1 | Maximum internal memory: 1 TB | On-board graphics card model: Aspeed AST2500 | Compliance certificates: RoHS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950