



Mikrotik cAP-2nD White Power over Ethernet (PoE)



Model: RBcAP2nD

Manufacturer: MIKROTIK

EAN: 4752224001191

Product Code: 325981

R1,528

Receiver sensitivity: 1MBit/s: -96 @ 22dBm Tx 11MBit/s: -89 @ 22dBm Tx 6MBit/s: -93 @ 20dBm Tx 54MBit/s: -74 @ 18dBm Tx MCS0: -93 @ 20dBm Tx MCS7: -71 @ 26dBm Tx | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -40 - 70 °C | Height: 31 mm | Warnings: Make sure the unit is stably mounted and ventilated. | AC input voltage: 11 - 57 V | Warnings: Do not use in damp conditions. | Warnings: Do not open the appliance - risk of electric shock. | 2.4 GHz: Yes | Mounting kit: Yes | Transmitting power: 22 dBmW | Depth: 138 mm | Placement: Ceiling | Operating system installed: RouterOS | Frequency band: 2.4 GHz | Width: 138 mm | PoE adapter included: Yes | 5 GHz: No | LED indicators: Yes | Auto MDI/MDI-X: Yes | Antenna gain level (max): 2 dBi | Power consumption (max): 4 W | Internal: No | Product colour: White | AC adapter included: Yes | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Wi-Fi data rate (max): 54 Mbit/s | Built-in processor: Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.11b | Internal memory: 64 MB | Flash memory: 16 MB | Power over Ethernet (PoE): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950