



Mikrotik cAP lite 54 Mbit/s White Power over Ethernet (PoE)



Model: RBcAPL-2nD

Manufacturer: MIKROTIK

EAN: 4752224003423

Product Code: 325982

R643

Receiver sensitivity: -96, -89, -93, -74, -71 | Placement: Ceiling, Wall | Depth: 20 mm | Width: 52 mm | Power over Ethernet (PoE): Yes | Harmonized System (HS) code: 85176990 | Internal: No | Internal memory: 64 MB | Operating system installed: RouterOS | Antenna gain level (max): 1.5 dBi | Power consumption (max): 4 W | Output voltage: 24 V | Flash memory: 16 MB | Height: 88 mm | Operating temperature (T-T): -40 - 70 °C | USB connector type: Micro-USB | Built-in processor: Yes | Reset button: Yes | Ethernet LAN data rates: 100 Mbit/s | 2.4 GHz: Yes | DC-in jack: Yes | AC input voltage: 10 - 60 V | Maximum data transfer rate: 54 Mbit/s | 5 GHz: No | Ethernet LAN (RJ-45) ports: 1 | Ethernet LAN data rates: 10 | Product colour: White | Antenna type: Internal | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.11b | Warnings: Do not open the appliance - risk of electric shock. | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not use in damp conditions.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950