

Mikrotik RB4011IGS+RM wired router Gigabit Ethernet Black

Model: RB4011iGS+RM

Manufacturer: MIKROTIK

EAN: 4752224002730

Product Code: 325987

R4,639

Product colour: Black | Rack capacity: 1U | DC-in jack: Yes | AC adapter included: Yes | Processor frequency: 1400 MHz | Ethernet LAN (RJ-45) ports: 10 | Power source type: DC, PoE | Ethernet LAN data rates: 10 | Operating temperature (T-T): -40 - 70 °C | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.3at | Security algorithms: SHA-256 | Security algorithms: 128-bit AES | Security algorithms: 256-bit AES | Security algorithms: SHA-1 | Reset button: Yes | LED indicators: Yes | Ethernet LAN data rates: 1000 | Installed SFP+ modules quantity: 1 | Cabling technology: 10/100/1000Base-T(X) | Voltage monitoring: Yes | 3G/4G USB modem compatibility: No | Height: 30 mm | Processor cores: 4 | License level: 5 | Operating system installed: RouterOS | Power over Ethernet (PoE) ports quantity: 2 | Temperature monitoring: Yes | Output voltage: 57 V | Width: 228 mm | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): Yes | Input voltage: 12 - 57 V | Depth: 120 mm | Ethernet LAN: Yes | SIM card slot: No | Ethernet interface type: Gigabit Ethernet | Ethernet WAN: Yes | Rack mounting: Yes | Built-in processor: Yes | Internal memory: 1024

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

MB | DSL WAN: No | Internal storage capacity: 0.5 GB | Processor model: Annapurna Labs Alpine AL21400 | Storage media: Flash | Serial ports quantity: 1 | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not open the appliance - risk of electric shock. | Power consumption (typical): 33 W | Warnings: Do not use in damp conditions. | Output current: 0.6 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950