

Ubiquiti UCG-Fiber (30W) gateway/controller 10, 100, 1000, 2500, 10000 Mbit/s

Ubiquiti UCG-Fiber (30W) gateway/controller 10, 100, 1000, 2500, 10000 Mbit/s



Model: UCG-Fiber

Manufacturer: UBIQUITI

EAN: 810177161288

Product Code: 326006

R7,030

Built-in processor: Yes | VLAN support: Yes | Firewall security: Yes | Multicast support: Yes | DC input voltage: 54 V | Display type: LCM | Number of processors installed: 1 | Power over Ethernet (PoE) type supported: PoE+ | Routing protocols: OSPF | Load balancing: Yes | Control display unit: Yes | Enclosure material: Polycarbonate (PC) | Export Control Classification Number (ECCN): EAR99 | Compliance certificates: CE | Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC) | Weight: 675 g | Ethernet LAN data rates: 1000 Mbit/s | Processor manufacturer: ARM | Input current: 1.1 A | Product colour: White | AC adapter included: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 10000 Mbit/s | Reset button: Yes | SFP+ ports quantity: 2 | Depth: 127.6 mm | Ethernet LAN data rates: 2500 Mbit/s | Electromagnetic (EMP) protection: Yes | Ethernet LAN data rates: 100 | Internal memory: 3000 MB | Quality of Service (QoS) support: Yes | Operating temperature (T-T): 0 - 40 °C | Input voltage: 100 - 240 V | Power over

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet (PoE): Yes | LED indicators: Status | Power consumption (max): 29.4 W | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 4 | Operating relative humidity (H-H): 5 - 95% | Electromagnetic (EMP) protection (air): 8 kV | Processor family: ARM Cortex | Width: 212.8 mm | WAN connection: Ethernet (RJ-45), SFP, SFP+ | Processor frequency: 2200 MHz | Security algorithms: IPSec | Security algorithms: TLS | Bluetooth: Yes | Security algorithms: 802.1x RADIUS | Display diagonal: 2.44 cm (0.96") | Electromagnetic (EMP) protection (contact): 4 kV | Cables included: Power | Height: 30 mm | Cables included: LAN (RJ-45)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950