



**SSD MICRON
SSD series 7500
MAX 1.6TB PCIe
Gen4 NVMe
NAND flash
technology 3D
NAND Write
speed 5300
MBytes/sec
Read speed
6800 MBytes/sec
Form Factor U.3
TBW 17520 TB
MTBF 2000000
hours
MTFDKCC3T2TGQ-
1BK1DABYYR**

Model: MTFDKCC3T2TGQ-1BK1DABYYR

Manufacturer: MICRON

Product Code: 332442

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

R16,197

The world's most advanced mainstream data center SSD

The Micron 7500 SSD is the world's first mainstream data center SSD with 200+ layer NAND. Micron's industry-first 232-layer NAND enables class-leading performance and higher power efficiency. It delivers best in class 6x9s QoS, with low and consistent sub-1 millisecond latency to enable rapid, reliable responsiveness for demanding data center workloads.

The Micron 7500 SSD accelerates workloads with class-leading PCIe® Gen4 speed in a U.3 form-factor with capacities ranging from 800GB to 15.36TB. It provides superior performance for workloads, such as AI, databases, content delivery, real-time analytics, social media platforms, cloud computing and virtualization.

A secure drive for an open compute world, the Micron 7500 SSD includes broad Open Compute Project (OCP) 2.0 support on its standard firmware. OCP provides intelligent management that facilitates rapid and proactive resolution of common data center challenges. The Micron 7500 SSD helps keep your data safe with key security features, like SPDM 1.2 attestation, SHA-512 and RSA standards, and Micron's Secure Encrypted Environment (SEE) which provides dedicated processing hardware with physical isolation for improved security.

The world's most advanced mainstream data center SSD

Leading-edge Micron technology and NAND deliver broad OCP standards support, efficiency and security. Micron 232-layer NAND enables increased performance and includes a 6-plane architecture with independent wordline read (iWL), which helps provide best-in-class random read latency that is up to 83% lower than competition. The Micron 7500 provides broad OCP 2.0 support for management at scale. Micron SEE and advanced security capabilities help keep your data safe.

Creating a new class of sub-1ms 6x9s latency drives

Low and consistent latency enables rapid, reliable responsiveness for demanding data center

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

workloads. The Micron 7500 SSD has sub-1 millisecond latency for 6x9s QoS and provides predictable performance for demanding workloads with increasing needs for low latency. The Micron 7500 SSD also has best-in-class 4K, random read latency versus competition, with RocksDB latency showing up to 54% better application response times than competing SSDs.

Accelerate your workloads with class-leading Gen4 speed

Superior performance for workloads, such as AI, databases, content delivery, real-time analytics, social media platforms, cloud computing and virtualization. The Micron 7500 drives RocksDB performance up to 2.1x better than other mainstream SSDs and has class-leading performance that beats the competition in random and sequential reads and writes.

Summary: Micron 7500 MAX. SSD capacity: 3.2 TB, SSD form factor: U.3, Read speed: 6800 MB/s, Write speed: 5300 MB/s, Component for: Server/workstation | Vendor Homepage:

<https://www.micron.com/products/storage/ssd/data-center-ssd/7500-ssd> | SSD disko talpa: 3200 |

SSD formos koeficientas: U.3 | Sąsaja: PCI Express 4.0 | NVMe: Taip | „NVMe“ versija: 2.0b |

Atminties tipas: 3D TLC NAND | Taikoma: Serveriui / darbo stočiai | Rašymo laikas: 5300 | Skaitymo

laikas: 6800 | Atsitiktinis skaitymas (4 KB): 1100 | Atsitiktinis rašymas (4 KB): 390 | Skaitymo delsa:

70 | Rašymo delsa: 15 | PCI „Express“ sąsajos duomenų keliai: x4 | S.M.A.R.T. palaikymas: Taip | Hot-

Plug palaikymas: Taip | Apsaugos algoritmų palaikymas: „TCG Enterprise“ | Plotis: 70.1 | Ilgis: 100.45

| Aukštis: 15 | Svoris: 200 | Darbo temperatūros diapazonas (TT): 0 - 70 | Bruto svoris: 0.2 | Neto

svoris: 0.2 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Name: SSD PCIE G4 U.3 NVME 3.2TB/7500

MAX MTFDKCC3T2TGQ MICRON | SSD series: 7500 MAX