

Switch MIKROTIK Rack 1x10Base-T 100Base-TX 24xSFP+ 2xQSFP+ 1xRJ45 CRS326-24S+2Q+RM

Model: CRS326-24S+2Q+RM

Manufacturer: MIKROTIK

EAN: 4752224002211

Product Code: 332662

R11,535

If you are working with substantial amount of data – like providing Internet access or maintaining a huge data center – this is the perfect upgrade for your setup. CRS326-24S+2Q+RM is our first product with 40 Gbps QSFP+ ports for remarkably fast and stable fiber connection.

Overall it has two 40 Gbps QSFP+ ports and twenty four 10 Gbps SFP+ ports, which provides total nonblocking throughput of 320 Gbps and switching capacity of 640 Gbps with forwarding rate of 252 Mpps with most common packets.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

CRS326-24S+2Q+RM is easy to manage – it has a full size USB port for configuration and dual power supply for redundancy – no unexpected downtime, your clients and colleagues will be thankful!

You can choose between our legendary feature-packed RouterOS for booting or a simpler, but still powerful SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS

Summary: Mikrotik CRS326-24S+2Q+RM. Switch type: Managed, Switch layer: L3. USB 2.0 ports quantity: 1, Console port: RJ-45. Switching capacity: 640 Gbit/s. Power connector: AC-in jack. Rack mounting, Form factor: 1U | Vendor Homepage: https://mikrotik.com/product/crs326_24s_2q_rm#fndtn-specifications | Perjungimo tipas: Valdomas | Perjungimo sluoksnis: L3 | SFP+ modulio angų kiekis: 24 | QSFP+ modulio angų kiekis: 2 | Konsolės prievadas: RJ-45 | USB 2.0 portų kiekis: 1 | Maitinimo jungtis: AC įėjimo lizdas | 10G parama: Taip | Perjungimo pajėgumas: 640 | Pralaidumas: 320 | Persiuntimo dažnis: 252 | Stovo montavimas: Taip | Forma: 1U | Produkto spalva: Balta | Atstatymo mygtukas: Taip | LED indikatoriai: Taip | Integruotas procesorius: Taip | Procesoriaus dažnis: 650 | Atminties tipas: RAM | Vidinė atmintis: 64 | Flash atmintis: 16 | Nereikalingos maitinimo (RPS) paramos: Taip | AC įėjimo įtampa: 100 - 240 | Galios suvartojimas (maks.): 69 | Maitinimas per Eternetą (PoE): Ne | Darbo temperatūros diapazonas (TT): -20 - 60 | Plotis: 443 | Ilgis: 183 | Aukštis: 44 | Pridėti kabeliai: AC | Stovo montavimo rinkinys: Taip | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 2.75 | Neto svoris: 2 | Vienetų skaičius vienoje siuntimo dėžėje: 10 | Vieneto plotis: 27.5 | Shipping Box Height: 28 | Vieneto gylis: 49 | Vieneto aukštis: 6.5 | Name: NET ROUTER/SWITCH 24SFP+/CRS326-24S+2Q+RM MIKROTIK

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950