



Switch MIKROTIK Type L3 Rack 24x10Base-T 100Base-TX 1000Base-T 4xSFP+ 1xRJ45 CRS328-24P- 4S+RM



Model: CRS328-24P-4S+RM

Manufacturer: MIKROTIK

EAN: 4752224002228

Product Code: 332733

R10,436

CRS328-24P-4S+RM is a 28 independent port switch, it has 24 Gigabit Ethernet ports, which offer different power output options: Passive PoE, low voltage PoE, 802.3af/at (Type 1 "PoE" / Type 2 "PoE+") with auto-sensing. PoE-Out is passed over mode B pins (4,5+)(7,8-). The four SFP+ ports provide up to 10 Gbps connectivity options via either optical fiber or Ethernet modules (not included).

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

CRS328-24P-4S+RM comes in a 1U rackmount case with 100-240 V AC 500 W power supply built-in. The device consumes up to 44 W leaving guaranteed 450 W (3x150 W per every 8 Ethernet ports) to power your PoE devices. Each port can provide up to 30 W of power with any power output option you choose.

The device has a “Dual boot” feature that allows you to choose between two operating systems - RouterOS or SwOS. If you prefer to have a simplified operating system with only switch specific features, use SwOS. If you would like the ability to use routing and other Layer 3 features in your CRS, use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings. All the feature set comes with disruptive price, providing best price/performance on the market.

- CPU temperature monitor
- Current Monitor
- PCB temperature monitor
- Voltage Monitor
- Mode button

Summary: Mikrotik CRS328-24P-4S+RM. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24, Console port: RJ-45. MAC address table: 16000 entries, Switching capacity: 128 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.3ad. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: https://mikrotik.com/product/crs328_24p_4s_rm | Switch type: Managed | Switch layer: L2/L3 | Quality of Service (QoS) support: Yes | System event log: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 4 | Console port: RJ-45 | Networking standards: IEEE 802.1Q/IEEE 802.3ad | Port mirroring: Yes | Auto-sensing: Yes | Broadcast storm control: Yes | Link aggregation: Yes | VLAN support: Yes | Number of VLANs: 4000 | Switching capacity: 128 | Throughput: 64000 | Forwarding rate: 95.2 | MAC address table: 16000 | Jumbo frames support: Yes | Jumbo frames: 10218 | Access Control List (ACL): Yes | IGMP snooping: Yes | Management protocols: SNMP | Rack mounting: Yes | Form factor: 1U | Product colour: White | LED indicators: Yes | Number of fans: 2 | Built-in processor: Yes | Processor manufacturer: ARM | Processor frequency: 800 | Internal memory: 512 | Flash memory: 16 | Mean time between failures (MTBF): 200000 | Power source: AC | Power supply included: Yes | Number of power supply units: 2 | AC input voltage: 100 -

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

240 | Power consumption (max): 44 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE/PoE+ | Power over Ethernet (PoE) ports quantity: 24 | Power over Ethernet (PoE) voltage: 26 | Power over Ethernet (PoE) power per port: 30 | Total Power over Ethernet (PoE) budget: 450 | Operating temperature (T-T): -20 - 60 | Width: 443 | Depth: 300 | Height: 44 | Cables included: AC | Rack mount kit: Yes | Harmonized System (HS) code: 85176990 | Unit Calculated Weight: 5.28 | Product Net Weight: 1.4 | Unit Calculated Volume: 0.03088 | Units per Shipping Box: 2 | Unit Width: 39 | Units per Pallet: 88 | Shipping Box Height: 26.5 | Unit Depth: 59 | Unit Height: 12.5 | Name: NET ROUTER/SWITCH 24 POE+/SFP+/CRS328-24P-4S+RM MIKROTIK

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950