



Switch MIKROTIK Type L3 CRS317-1G- 16S+RM



Model: CRS317-1G-16S+RM

Manufacturer: MIKROTIK

EAN: 4752224002167

Product Code: 332785

R9,311

The new Cloud Router Switch 317-1G-16S+RM is a rack-mountable manageable switch with Layer3 features, it has 16 SFP+ ports for high performance 10GbE connectivity and a 1GbE copper port for management.

CRS317-1G-16S+RM is powered by a next generation switching chip, giving you wire speed performance for all sixteen 10GbE ports with any Ethernet frame size. New features such as hardware-based Spanning Tree Protocol and Link Aggregation (LACP) provide enhanced protection and true professional performance for your demanding network.

The unit has dual redundant power supplies and passive cooling case, so it's completely silent - for hot environments two redundant fans will automatically keep the system cool if needed.

Summary: Mikrotik CRS317-1G-16S+RM. Switch type: Managed, Switch layer: L3. Console port: RJ-45. Networking standards: IEEE 802.1Q. Power connector: DC-in jack. Rack mounting, Form factor:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

1U | Vendor Homepage: https://mikrotik.com/product/crs317_1g_16s_rm | Switch layer: L3 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports type: No | Console port: RJ-45 | Gigabit Ethernet (copper) ports quantity: 1 | Power connector: DC-in jack | SFP+ module slots quantity: 16 | 10G support: Yes | Broadcast storm control: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1Q | Number of VLANs: 4000 | Port mirroring: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Security algorithms: SNMPv2/SNMPv3 | Form factor: 1U | LED indicators: Yes | Number of fans: 2 | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | Built-in processor: Yes | Flash memory: 1000 | Internal memory: 16 | Memory type: Flash | Processor frequency: 800 | AC input voltage: 110 - 240 | Number of power supply units: 2 | Power consumption (max): 42 | Power over Ethernet (PoE): No | Operating temperature (T-T): -20 - 60 | Depth: 224 | Height: 44 | Width: 443 | Cables included: AC | User guide: Yes | Mounting brackets included: Yes | Harmonized System (HS) code: 85176990 | Product Net Weight: 1.4 | Shipping Box Height: 29.5 | Unit Calculated Volume: 0.008496 | Unit Calculated Weight: 2.43 | Units per Shipping Box: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950