

Dahua Technology CS4228-24GT-240 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Model: CS4228-24GT-240

Manufacturer: DAHUA

EAN: 6923172571212

Product Code: 332848

R5,323

- Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab,IEEE802.3z standards

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE, and IEEE802.3bt power supply standards
- Manages PoE power consumption and PoE power on/off. Supports Intelligent PoE
- A wide operating temperature range and a full metal casing that is fully-enclosed and dust-proof

Summary: Dahua Technology CS4228-24GT-240. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 26, Installed SFP modules quantity: 2. MAC address table: 8000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Power over Ethernet (PoE). Rack mounting | Vendor Homepage: https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CS4228-24GT-240 | Switch type: Managed | Switch layer: L2 | Cloud-managed: Yes | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP modules quantity: 2 | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | 10G support: No | Flow control support: Yes | VLAN support: Yes | Virtual LAN features: Port-based VLAN | Number of VLANs: 32 | Switching capacity: 56 | Forwarding rate: 41.66 | MAC address table: 8000 | Jumbo frames support: Yes | Jumbo frames: 15360 | DHCP features: DHCP client | Rack mounting: Yes | Product colour: Black | Housing material: Steel | Power source: AC/DC/PoE | AC input voltage: 100 - 240 | AC input frequency: 47/63 | Input current: 4 | Power consumption (max): 265 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 24 | Total Power over Ethernet (PoE) budget: 240 | Operating temperature (T-T): -10 - 55 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 5 - 95 | Storage relative humidity (H-H): 5 - 95 | Width: 440 | Depth: 220 | Height: 44 | Weight: 2500 | Package width: 540 | Package depth: 342 | Package height: 90 | Package weight: 3150 | Unit Calculated Weight: 3.67 | Product Net Weight: 2.5 | Unit Calculated Volume: 0.01918 | Units per Shipping Box: 5 | Unit Width: 34 | Units per Pallet: 0 | Shipping Box Height: 36.7000007629395 | Unit Depth: 54 | Unit Height: 9 | Name: NET SWITCH 28PORT 24POE/CS4228-24GT-240 DAHUA | Model name: CS4228-24GT-240

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950