

NET ROUTER/SWITCH 18PORT/CRS318-16P-2S+OUT MIKROTIK

Model: CRS318-16P-2S+OUT

Manufacturer: MIKROTIK

EAN: 4752224002174

Product Code: 333243

R5,812

Powering a bunch of access points or IP cameras and a few uplinks on a tower has never been easier. netPower 16P has 16 Gigabit Ethernet ports with PoE-out and two SFP+ ports for 10G fiber uplinks.

Its sturdy and compact outdoor enclosure allows the switch to be mounted in all kinds of environments – from damp attics and shafts to towers, masts and poles with hose clamps.

netPower 16P has a non-blocking throughput of 36 Gbps, switching capacity of 72 Gbps and forwarding rate of 53.6 Mpps.

Device itself does not have onboard voltage converter. You need 24V PSU to have 24V PoE out

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

and/or 48V PSU to have 48V PoE out (IEEE 802.3 at/af).

* Power supply is NOT included with the product. You are welcome to use your preferred power option, like battery pack etc. Compatible also with MikroTik power supplies 24HPOW, 48POW and 48V2A96W

Summary: Mikrotik netPower 16P. Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Switching capacity: 72 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 18 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE) | Vendor Homepage: https://mikrotik.com/product/netpower_16p#fndtn-specifications | Switch layer: L2/L3 | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 2 | Power connector: DC-in jack | Networking standards: IEEE 802.3af/IEEE 802.3at | 10G support: No | Switching capacity: 72 | Forwarding rate: 53.6 | Rack mounting: No | Stackable: No | Product colour: White | Temperature sensor: Yes | Built-in processor: Yes | Processor model: 98DX226S | Processor frequency: 800 | Internal memory: 256 | Flash memory: 16 | Power supply included: Yes | DC input voltage: 18 - 57 | Power consumption (max): 316 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 16 | Operating temperature (T-T): -40 - 70 | Width: 212 | Depth: 78 | Height: 303 | Certification: CE/RED, EAC, RoHS | Unit Calculated Weight: 3.03 | Product Net Weight: 2 | Unit Calculated Volume: 0.01219 | Units per Shipping Box: 5 | Unit Width: 9.7 | Units per Pallet: 0 | Shipping Box Height: 46 | Unit Depth: 40 | Unit Height: 24.7 | Name: NET ROUTER/SWITCH 18PORT/CRS318-16P-2S+OUT MIKROTIK | Model: CRS318-16P-2S+OUT

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950