

Access Point MIKROTIK 300 Mbit/s 1xLAN ports LTAP-2HND&FG621-EA&LR8G

Access Point MIKROTIK 300 Mbit/s 1xLAN ports LTAP- 2HND&FG621- EA&LR8G



Model: LTAP-2HND&FG621-EA&LR8G

Manufacturer: MIKROTIK

EAN: 4752224009913

Product Code: 333309

R5,224

A rugged all-in-one device for IoT connectivity, ideal for industrial or public use. Perfect for transportation projects or logistics, the LtAP LR8G LTE6 Kit combines:

- LoRa® connectivity, LTE, and GPS for maximum versatility
- Dual-chain 2.4 GHz WiFi for added flexibility
- A tough, robust enclosure built for industrial and mobile setups
- Mini SIM slot and a built-in modern LTE6 modem for fast and responsive mobile connectivity
- Enhanced 868MHz Rx sensitivity for effective long-range communication
- Many powering options, including automotive
- SMA female connectors for external antennas

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

The Things Network

Our products for LoRa® are ready to work with “The Things Network” - the famous open source infrastructure that provides free LoRa® network coverage and has tons of apps for your needs. With the help of “The Things Network” you can get started with the Internet-of-things within a day. And it is easily upgradable to enterprise-grade network “The Things Industries”.

The setup is so easy - anyone can learn it. No need to reinvent the wheel – join “The Things Network” to save time and energy with smart solutions!

Summary: Mikrotik LtAP LR8G LTE6 kit. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: Black. Power consumption (max): 24 W | Vendor Homepage: https://mikrotik.com/product/ltap_lr8g_lte6_kit | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Maximum data transfer rate: 300 | Ethernet LAN data rates: 10/100/1000 | Cabling technology: 10/100/1000Base-T(X) | GPS (satellite): Yes | Mean time between failures (MTBF): 200000 | Ethernet LAN (RJ-45) ports: 1 | USB 2.0 ports quantity: 1 | USB connector type: USB Type-A | RS-232 interface: Yes | DC-in jack: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | DC voltage range: 12 - 30 | Power consumption (max): 24 | Product colour: Black | International Protection (IP) code: IPX0 | Built-in processor: Yes | Processor model: MediaTek MT7621AT | Processor frequency: 880 | Flash memory: 16 | Internal memory: 128 | Operating system installed: RouterOS | 3G bands supported: 850,900,2100,1800 | 4G LTE category: 6 | 4G FDD-LTE bands supported: 2100,1800,850,2600,900,800,700 | 4G TDD-LTE bands supported: 2600,2300,2500 | SIM card slot: Yes | SIM card type: MiniSIM | Compliance certificates: CE/EAC/RoHS | Quantity per pack: 1 | AC adapter included: Yes | Mounting kit: Yes | Unit Calculated Weight: 1.11 | Product Net Weight: 0.5 | Unit Calculated Volume: 0.003413 | Units per Shipping Box: 10 | Unit Width: 19 | Units per Pallet: 0 | Shipping Box Height: 32 | Unit Depth: 29 | Unit Height: 5 | Name: WRL ACCESS POINT LTE6 KIT/LTAP2HND&FG621EA&LR8G MIKROTIK | Model: LTAP-2HND&FG621-EA&LR8G | Model name: LtAP LR8G LTE6 kit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950