

NET ROUTER 1000M 7PORT/RB5009UG+S+IN MIKROTIK

NET ROUTER

1000M

7PORT/RB5009UG+S+IN

MIKROTIK



Model: RB5009UG+S+IN

Manufacturer: MIKROTIK

EAN: 4752224007148

Product Code: 333481

R4,567

Double the usual performance: we took your feedback from the MikroTik User Meetings to create the perfect home lab router: compact, powerful, with multiple powering options and efficient cooling. RB5009 has it all, and even more!

The board features 9 wired ports and a full-sized USB 3.0. Seven of the ports are Gigabit Ethernet, another one is 2.5 Gigabit Ethernet, and the last one is a 10G SFP+ cage. All the ports are connected to a powerful Marvell Amethyst family switch-chip with a 10 Gbps full-duplex line leading to the Marvell Armada Quad-core ARMv8 1.4 GHz CPU. Both CPU and the switch-chip are located on the bottom of the board – so the case acts as a massive heat-sink!

RB5009UG+S+IN can be powered in 3 different ways:

a) PoE-in from Ethernet port #1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

b) DC Jack

c) 2-pin terminal on the side

Boards come with 1GB of DDR4 RAM and 1GB NAND storage. This combination of ports and components, compared to our other products in a similar form factor, provides almost double the performance in configurations with heavy CPU loads.

With a simple set of mounting accessories, you can mount FOUR of these routers in a single 1U rackmount space! No more server-room-Tetris, just pure productivity.

Summary: Mikrotik RB5009UG+S+IN. Networking standards: IEEE 802.3af, IEEE 802.3at, Ethernet interface type: 2.5 Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s. USB version: 3.2 Gen 1 (3.1 Gen 1). Compliance certificates: RoHS. Mean time between failures (MTBF): 200000 h, Certification: CE, EAC, ROHS. Product colour: Black | Vendor Homepage: https://mikrotik.com/product/rb5009ug_s_in#fndtn-specifications | Ethernet WAN: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet LAN data rates: 10/100/1000 | Mobile network generation: Not supported | Ethernet LAN (RJ-45) ports: 1 | Gigabit Ethernet (copper) ports quantity: 7 | Power over Ethernet (PoE) ports quantity: 1 | Installed SFP+ modules quantity: 1 | USB ports quantity: 1 | USB version: 3.2 Gen 1 (3.1 Gen 1) | DC-in jack: Yes | Compliance certificates: RoHS | Mean time between failures (MTBF): 200000 | Certification: CE, EAC, ROHS | Product colour: Black | Power consumption (typical): 20 | Power source type: DC | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 60 | Harmonized System (HS) code: 85176990 | Unit Calculated Weight: 0.902 | Product Net Weight: 0.6 | Unit Calculated Volume: 0.00256 | Units per Shipping Box: 20 | Unit Width: 13.5 | Units per Pallet: 0 | Shipping Box Height: 34.5 | Unit Depth: 31.5 | Unit Height: 5 | Name: NET ROUTER 1000M 7PORT/RB5009UG+S+IN MIKROTIK | Product model code: RB5009UG+S+IN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950