



NET ROUTER 1000M 10PORT 1SFP+/RB4011IGS+RM MIKROTIK



Model: RB4011IGS+RM

Manufacturer: MIKROTIK

EAN: 4752224002730

Product Code: 333483

R4,045

RB4011 series - amazingly powerful routers with ten Gigabit ports, SFP+ 10Gbps interface and IPsec hardware acceleration for a great price!

The RB4011 uses a quad core Cortex A15 CPU, same as in our carrier grade RB1100AHx4 unit. The unit is equipped with 1GB of RAM, can provide PoE output on port #10 and comes with a compact and professional looking solid metal enclosure in matte black.

RB4011iGS+RM (Ethernet model) includes two rackmount ears that will securely fasten the unit in a standard 1U rack space.

Summary: Mikrotik RB4011IGS+RM. Networking standards: IEEE 802.3at, Ethernet interface type: Gigabit Ethernet, Cabling technology: 10/100/1000Base-T(X). Security algorithms: 128-bit AES, 256-bit AES, SHA-1, SHA-256. Processor model: Annapurna Labs Alpine AL21400, Processor frequency: 1400 MHz, Storage media: Flash. Product colour: Black, Rack capacity: 1U. Power consumption

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(typical): 33 W, Power source type: DC, PoE, Output voltage: 57 V | Vendor Homepage: https://mikrotik.com/product/rb4011igs_rm#fndtn-specifications | 3G/4G USB modem compatibility: No | DSL WAN: No | Ethernet WAN: Yes | SIM card slot: No | Cabling technology: 10/100/1000Base-T(X) | Ethernet interface type: Gigabit Ethernet | Ethernet LAN: Yes | Ethernet LAN data rates: 10/100/1000 | Networking standards: IEEE 802.3at | Reset button: Yes | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 10 | Installed SFP+ modules quantity: 1 | Power over Ethernet (PoE) ports quantity: 2 | Serial ports quantity: 1 | Security algorithms: 128-bit AES/256-bit AES/SHA-1/SHA-256 | AC adapter included: Yes | Built-in processor: Yes | Internal memory: 1024 | Internal storage capacity: 0.5 | License level: 5 | Operating system installed: RouterOS | Processor cores: 4 | Processor frequency: 1400 | Processor model: Annapurna Labs Alpine AL21400 | Storage media: Flash | Temperature monitoring: Yes | Voltage monitoring: Yes | LED indicators: Yes | Product colour: Black | Rack capacity: 1U | Rack mounting: Yes | Output current: 0.6 | Output voltage: 57 | Power consumption (typical): 33 | Power over Ethernet (PoE): Yes | Power source type: DC,PoE | Operating temperature (T-T): -40 - 70 | Depth: 120 | Height: 30 | Width: 228 | Harmonized System (HS) code: 85176990 | Input voltage: 12 - 57 | Units per Pallet: 80 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.003014 | Unit Calculated Weight: 1.02

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950