

NET ROUTER/SWITCH 24PORT 1000M/CRS326-24G-2S+RM MIKROTIK

Model: CRS326-24G-2S+RM

Manufacturer: MIKROTIK

EAN: 4752224002198

Product Code: 333498

R4,621

SwOS/RouterOS powered 24 port Gigabit Ethernet switch with two SFP+ ports, wire speed connectivity with several new switching features!

It has “Dual boot” feature that allows you to choose which operating system you prefer to use, RouterOS or SwOS. If you prefer to have a simplified switch only OS with more switch specific features, use SwOS. If you are used to Winbox and would like the ability to use routing and other Layer 3 features on some ports in your CRS, boot and use RouterOS. You can select the desired operating system from RouterOS, from SwOS or from the RouterBOOT loader settings.

It gives you all the basic functionality for a managed switch, plus more: allows to manage port-to-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields. SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.

Summary: Mikrotik CRS326-24G-2S+RM. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24, Console port: RJ-45. Networking standards: IEEE 802.1Q | Vendor Homepage: https://mikrotik.com/product/CRS326-24G-2SplusRM | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Console port: RJ-45 | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Networking standards: IEEE 802.1Q | Number of VLANs: 4000 | Port mirroring: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Access Control List (ACL): Yes | Security algorithms: SNMP | Product colour: Grey | Built-in processor: Yes | Compatible operating systems: RouterOS, SwitchOS | Flash memory: 16 | Internal memory: 512 | Processor frequency: 800 | Power consumption (max): 24 | Power supply included: Yes | Operating temperature (T-T): -40 - 60 | Depth: 144 | Height: 44 | Width: 440 | Rack mount kit: Yes | AC adapter included: Yes | Harmonized System (HS) code: 85176990 | Product Net Weight: 1.4 | Shipping Box Height: 22 | Unit Calculated Volume: 0.0088 | Unit Calculated Weight: 1.7 | Units per Shipping Box: 10

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950