



Switch MIKROTIK CRS326-24G- 2S+IN 24x10Base-T 100Base-TX 1000Base-T 2xSFP+ CRS326- 24G-2S+IN

Model: CRS326-24G-2S+IN

Manufacturer: MIKROTIK

EAN: 4752224006462

Product Code: 333525

R3,890

A home network setup doesn't have to be a compromise. This compact and quiet switch is packing some serious server room grade features: a pair of 10G SFP+ cages, 512 MB of RAM, 24 Gigabit Ethernet ports and a sufficient built-in CPU that can handle basic home user needs such as firewall, NAT and even some VPN. And it is extremely affordable – we are keeping the price on par with the previous generation desktop switches!

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Like many other MikroTik switches, CRS326-24G-2S+IN offers the dual boot option that allows you to use either the lightweight SwOS or the advanced RouterOS. The compact and quiet fanless desktop case makes this switch the perfect addition to the best home setups. And it is very easy to transport! But make no mistake – this small switch has all the power and features of its bigger rackmount analogue – the CRS326-24G-2S+RM, nothing has been removed!

CRS326-24G-2S+IN provides all the basic functionality for a managed switch, and even more: port-to-port forwarding, MAC filtering, VLAN configuration, traffic mirroring, bandwidth limitation and even adjust some MAC and IP header fields. SFP+ cage supports both 1.25G SFP and 10G SFP+ modules.

Summary: Mikrotik CRS326-24G-2S+IN. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. DC input voltage: 10 - 30 V. Power over Ethernet (PoE). Rack mounting | Vendor Homepage:

https://mikrotik.com/product/crs326_24g_2s_in | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 2 | 10G support: Yes | Ethernet LAN data rates: 1000 | IP routing: Yes | Port mirroring: Yes | Rate limiting: Yes | VLAN support: Yes | MAC address filtering: Yes | Product colour: White | Rack mounting: Yes | Built-in processor: Yes | Flash memory: 16 | Internal memory: 512 | Memory type: DDR3-SDRAM | DC input voltage: 10 - 30 | Input current: 1.2 | Number of power supply units: 2 | Power consumption (max): 21 | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Power over Ethernet (PoE) voltage: 30 | Operating temperature (T-T): -40 - 60 | Depth: 144 | Height: 44 | Width: 285 | Certification: CE/RED, EAC, ROHS | Model name: CRS326-24G-2S+IN | Units per Shipping Box: 1 | Unit Calculated Volume: 0.005392 | Unit Calculated Weight: 1.31