



Switch MIKROTIK 1x10Base-T 100Base-TX 1000Base-T 4xSFP+ 1xConsole CRS305-1G- 4S+OUT

Model: CRS305-1G-4S+OUT

Manufacturer: MIKROTIK

EAN: 4752224006523

Product Code: 333554

R4,811

Ultimate value pick for 10 Gigabit outdoor networking. High masts, poles, or towers – your connection will be safe! A powerful budget version of the netFiber 9.

There are two ways to look at the brand new Fiber Box Plus. On the one hand, it's a massive upgrade of our previous FiberBox devices. This version features a modern ARM CPU, more RAM, and four 10-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Gigabit SFP+ ports. Fast and reliable connectivity on a budget. Without the distance limitations of Ethernet. There's also a Gigabit Ethernet port for management purposes or PoE-in powering. We've also included a 2-pin terminal and a standard DC jack, so you have 3 different power options to choose from. FiberBox Plus supports a wide input voltage range of 24-57V. And it is remarkably efficient: maximum power consumption (without attachments) is only 7W.

Another way to look at the new FiberBox Plus – it's a budget version of the amazing netFiber 9. You can save a lot of money if you don't need the extra Gigabit SFP ports. It even features the same impressive Marvell 98DX226S switch-chip, so the performance is definitely there!

This rugged outdoor switch is perfect for connecting mast devices. Like the mANTBox 52 or the LHG XL 52. Imagine a huge campsite with several guest houses, a food court, and the owner's cabin. You can connect all the locations with the FiberBox Plus. One of the fiber connections can be used for the mANTBox base station – to provide general connectivity for the guests. Another connection could go to the owner's house. And the third could be used in the food court – to connect their payment and inventory servers.

Usually, you would need some kind of a junction box to keep everything safe. But our FiberBox Plus comes with a solid water resistance rating of IP66. That means protection against powerful water jets from any direction. So in the campsite scenario, your setup is not only safe from all kinds of crazy weather, but it can also withstand young pranksters with a garden hose. Not to mention damp basements, elevator shafts, seaport infrastructure, and so on. With FiberBox Plus, you have nothing to worry about.

Summary: Mikrotik FiberBox Plus. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 1. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 24 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE) | Vendor Homepage: <https://mikrotik.com/product/fiberboxplus#fndtn-specifications> | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 1 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 4 | Power connector: DC-in jack | Networking standards: IEEE 802.3af/IEEE 802.3at | 10G support: Yes | Rack mounting: No | Stackable: No | Product colour: White | Temperature sensor: Yes | Operating system installed: RouterOS | Built-in processor: Yes | Processor manufacturer: ARM | Processor model: 98DX226S | Processor frequency: 800 | Internal memory: 256 | Flash memory: 16 | Minimum

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

RAM: 256 | Power source: DC/PoE | Power supply included: Yes | DC input voltage: 24 - 57 | Power consumption (typical): 7 | Power consumption (max): 17 | Power over Ethernet (PoE): Yes | Operating temperature (T-T): -40 - 70 | Unit Calculated Weight: 2.6 | Product Net Weight: 0.45 | Unit Calculated Volume: 0.008977 | Units per Shipping Box: 1 | Unit Width: 22.5 | Shipping Box Height: 9.5 | Unit Depth: 42 | Unit Height: 9.5 | Name: NET ROUTER/SWITCH 4 SFP+/CRS305-1G-4S+OUT MIKROTIK | Model: CRS305-1G-4S+OUT

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950