

Switch MIKROTIK CSS326-24G-2S+RM Switch type Managed Rack mounting Yes Form factor 1U 24xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) 2xSFP+ module slots quantity 10G support Yes Power over Ethernet (PoE) Yes CSS326-24G-2S+RM

Model: CSS326-24G-2S+RM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Manufacturer: MIKROTIK

EAN: 4752224002334

Product Code: 333812

R3,656

SwOS powered 24 port Gigabit Ethernet switch with two SFP+ ports, wire speed connectivity with several new switching features.

The device is powered by a Marvell DX switch chip. The device is running an operating system designed specifically for MikroTik switch products - SwOS. SwOS is configurable from your web browser. It gives you all the basic functionality for a managed switch, plus more: allows to manage port-to-port forwarding, apply MAC filter, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields. SFP cage supports both 1.25 Gb SFP and 10 Gb SFP+ modules.
Summary: Mikrotik CSS326-24G-2S+RM. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. Networking standards: IEEE 802.1Q. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: https://mikrotik.com/product/CSS326-24G-2SplusRM | Perjungimo tipas: Valdomas | Web pagrįstas valdymas: Taip | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 24 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Gigabit Ethernet (10/100/1000) | SFP+ modulio angų kiekis: 2 | Maitinimo jungtis: DC lizdas | Tinklo standartai: IEEE 802.1Q | 10G parama: Taip | Portų mirroring: Taip | Aprėpties medžio protokolas: Taip | Transliacijos audros valdymas: Taip | VLAN palaikymas: Taip | VLANs skaičius: 4000 | Prieigos kontrolės sąrašas (ACL): Taip | Apsaugos algoritmų palaikymas: SNMP | MAC adresų filtravimas: Taip | Stovo montavimas: Taip | Forma: 1U | Produkto spalva: Balta | Atstatymo mygtukas: Taip | Integruotas procesorius: Taip | Vidinė atmintis: 2 | Flash atmintis: 2 | Maitinimo šaltinis: DC/PoE | Pridėtas maitinimo šaltinis: Taip | Maitinimo šaltinių skaičius: 1 | Energijos suvartojimas: 19 | Maitinimas per Eternetą (PoE): Taip | Palaikomas maitinimo per eternetą (en. PoE) tipas: Passive PoE | Maitinimo per

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Eternetą (PoE) įtampos diapazonas: 10 - 30 | Darbo temperatūros diapazonas (TT): -40 - 70 | Plotis: 440 | Ilgis: 144 | Aukštis: 44 | Instrukcija: Taip | Kintamosios srovės adapteris: Taip | Pridėti montavimo kronšteinai: Taip | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 1.86 | Neto svoris: 1.5 | Vienetų skaičius vienoje siuntimo dėžėje: 10 | Vieneto plotis: 20 | Shipping Box Height: 22 | Vieneto gylis: 56 | Vieneto aukštis: 7 | Name: NET SWITCH 24PORT 1000M 2SFP+/CSS326-24G-2S+RM MIKROTIK | Model name: CSS326-24G-2S+RM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950