TP-Link Omada EAP650-DESKTOP wireless access point 2976 Mbit/s White Power over Ethernet (PoE)

Model: EAP650-DESKTOP

Manufacturer: TP-LINK

EAN: 8885020623734

Product Code: 333904

R3,140

- Blazing-Fast AX3000 WiFi 6 Speeds: 574 Mbps on 2.4 GHz and 2402 Mbps on 5GHz totals 2976 Mbps WiFi speeds. †
- Multiple Gigabit Ports: Connect multiple devices with 4× Gigabit Ethernet Ports
- Convenient Deployment: Supports both 802.3bt PoE++ and DC (adapter included) for easy and quick deployment
- No Installation needed:Supports desktop installation without the need for additional setup

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- High Flexibility: Provide flexible installation solutions for both desktop and wall mounting
- Stay Smooth with Seamless Roaming: Users can enjoy seamless streaming across the property with their devices switching effortlessly between access points.§
- Centralized Cloud Management: Integrates with the Omada SDN platform for Centralized Management. §

Summary: TP-Link Omada EAP650-DESKTOP. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2976 Mbit/s. Security algorithms: 802.1x RADIUS, SNMP, SNMPv2, SNMPv3, SSH, WPA-Enterprise, WPA-Personal, WPA2-Enterprise,.... Ethernet LAN data rates: 1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 17.3 W | Vendor Homepage: https://www.omadanetworks.com/my/business-networking/omada-wifi-desktop/eap650-desktop/ | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Maximum data transfer rate: 2976 | Maximum data transfer rate (2.4 GHz): 574 | Maximum data transfer rate (5 GHz): 2402 | Ethernet LAN data rates: 1000 | Networking standards: IEEE 802.3af/IEEE 802.3bt | Channel bandwidth: 160 | MIMO: Yes | MIMO type: Multi User MIMO | VLAN support: Yes | Rate limiting: Yes | Load balancing: Yes | Band steering: Yes | Airtime Fairness (ATF): Yes | Quality of Service (QoS) support: Yes | BeamForming: Yes | Transmitting power (CE): 20 - 29 | Transmitting power (FCC): 26 - 27 | Security algorithms: 802.1x RADIUS/SNMP/SNMPv2/SNMPv3/SSH/WPA2-Enterprise/WPA2-Personal/WPA3-Enterprise/WPA3-Personal/WPA-Enterprise/WPA-Personal | Service Set Identifier (SSID) features: Multiple SSIDs | Number of SSID supported: 16 | Access Control List (ACL): Yes | Web-based management: Yes | Syslog: Yes | Management platform: Omada | Ethernet LAN (RJ-45) ports: 4 | Power over Ethernet (PoE): Yes | DC voltage range: 12 | Input current: 1.5 | Power consumption (max): 17.3 | Placement: Table | Product colour: White | Reset button: Yes | LED indicators: Yes | Antenna type: Internal | Antenna gain level (max): 4.7 | Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux | Certification: CE, FCC, RoHS, IC | Width: 140 | Depth: 33 | Height: 175 | Weight: 452 | Quantity per pack: 1 | Wireless standard: IEEE 802.11 a/b/g/n/ac/ax | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -40 - 70 | Storage relative humidity (H-H): 5 - 90 | Unit Calculated Weight: 0.921 | Product Net Weight: 0.452 | Unit Calculated Volume: 0.003491 | Units per Shipping Box: 1 | Unit Width: 17.5 | Shipping Box Height: 9.5 | Unit Depth: 21 | Unit Height: 9.5 | Name: WRL ACCESS POINT 3000MBPS/OMADA EAP650-DESKTOP TP-LINK | Series: Omada | Model name: EAP650-DESKTOP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950