

Switch MIKROTIK netPower Lite 7R 8xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) 2xSFP+ module slots quantity 10G support Yes Power over Ethernet (PoE) Yes CSS610-1GI-7R-2S+OUT



Switch MIKROTIK netPower Lite 7R 8xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) 2xSFP+ module slots quantity 10G support Yes Power over Ethernet (PoE) Yes CSS610-1GI- 7R-2S+OUT

Model: CSS610-1GI-7R-2S+OUT

Manufacturer: MIKROTIK

EAN: 4752224000033

Product Code: 333956

R3,188

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

With netPower Lite 7R switch you can forget about expensive GPON base stations and optical splitters. This switch is a part of our GPEN concept – aimed to bring the speed and versatility of fiber networking while using the advantages of Ethernet. It is an easy to deploy, low-cost way for any ISP to deliver the Internet to individual apartments.

With this switch you won't have to worry about power issues, as there are many options. netPower Lite 7R has 7 reverse PoE ports. Depending on your setup, netPower can draw the necessary power even from a single client! Ethernet port 8 can power other PoE capable devices with the same voltage as applied to the unit. There is also a DC jack and a 2-pin terminal for alternative powering.

The outdoor enclosure allows you to install this switch in all kinds of environments – from damp attics to elevator shafts and different poles with hose clamps. netPower Lite 7R has a non-blocking throughput of 28 Gbps, switching capacity of 56 Gbps and forwarding rate of 41.7 Mpps.

Summary: Mikrotik netPower Lite 7R. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. DC input voltage: 12 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE) | Vendor Homepage:

https://mikrotik.com/product/netpower_lite_7r#fndtn-specifications | Product Net Weight: 1.6 | Shipping Box Height: 40 | Unit Calculated Volume: 0.007072 | Unit Calculated Weight: 2.18 | Units per Pallet: 0 | Units per Shipping Box: 5 | Product model code: CSS610-1Gi-7R-2S+OUT // netPower Lite 7R