



TP-Link 16-Port Gigabit Desktop Switch with 16-Port PoE+



Model: TL-SG116P

Manufacturer: TP-LINK

EAN: 4895252500301

Product Code: 333969

R3,318

NET SWITCH 16PORT 1000M POE+/TL-SG116P TP-LINK

- With 16 PoE+ ports, transfers data and power on one single cable
- Compliance with IEEE 802.3af/at PoE+, the switch supports PoE Power up to 30 W for each PoE port
- Supports PoE Power up to 120 W for all PoE ports*
- Up to 250 m data and power transmission range under Extend Mode**
- Priority Mode ensures high priority of ports 1-4 to guarantee the quality of the sensitive applications
- Isolation Mode allows one-click client traffic separation for higher security and performance
- Automatically reboots your dropped or unresponsive PoE-powered devices with PoE Auto Recovery
- Plug and play with no configuration required

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Summary: TP-Link 16-Port Gigabit Desktop Switch with 16-Port PoE+. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. MAC address table: 8000 entries, Switching capacity: 32 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. DC input voltage: 9 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://www.tp-link.com/au/business-networking/unmanaged-switch/tl-sg116p/> | Switch type: Unmanaged | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 16 | Networking standards: IEEE 802.1p/IEEE 802.1Q/IEEE 802.3/IEEE 802.3ab/IEEE 802.3u | Copper ethernet cabling technology: 1000BASE-T/100BASE-TX/10BASE-T | Cable types supported: Cat3/Cat4/Cat5/Cat5e/Cat6 | Port mirroring: Yes | Full duplex: Yes | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Cable length detection: Yes | Flow control support: Yes | Link aggregation: Yes | Rate limiting: Yes | VLAN support: Yes | Virtual LAN features: Protocol-based VLAN/Tagged VLAN | Number of VLANs: 32 | Switching capacity: 32 | Forwarding rate: 23.81 | MAC address table: 8000 | Store-and-forward: Yes | Number of queues: 4 | Jumbo frames support: Yes | Jumbo frames: 9000 | Packet buffer memory: 4.1 | IGMP snooping: Yes | Loop protection: Yes | Stackable: Yes | Product colour: Black | Housing material: Metal | LED indicators: Yes | Wall mountable: Yes | Power supply included: Yes | AC input voltage: 220 | AC input frequency: 50 | DC input voltage: 9 | Input current: 0.6 | Power consumption (typical): 11.72 | Power consumption (max): 144.28 | Power over Ethernet (PoE): Yes | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -40 - 70 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 90 | Heat dissipation: 490.55 | Width: 286 | Depth: 111.7 | Height: 25.4 | Quick start guide: Yes | Package width: 227 | Package depth: 434 | Package height: 70 | Package weight: 2000 | Unit Calculated Weight: 2.27 | Product Net Weight: 0.94 | Unit Calculated Volume: 0.008645 | Units per Shipping Box: 6 | Unit Width: 7 | Units per Pallet: 0 | Shipping Box Height: 24 | Unit Depth: 43.5 | Unit Height: 23 | Name: NET SWITCH 16PORT 1000M POE+/TL-SG116P TP-LINK | Model: TL-SG116P

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950