

Switch MIKROTIK 16x10Base-T 100Base-TX 1000Base-T CSS318-16G-2S+IN



Switch MIKROTIK 16x10Base-T 100Base-TX 1000Base-T CSS318-16G- 2S+IN

Model: CSS318-16G-2S+IN

Manufacturer: MIKROTIK

EAN: 4752224009227

Product Code: 333988

R3,133

With 16 Gigabit Ethernet ports and 2 SFP+ 10G uplink ports, you get all the connectivity you need without unnecessary bulk. Stack two units side by side in a single 1U rack space for even greater flexibility and scalability.

The CSS318-16G-2S+IN is a perfect fit for setups where 24 ports are too many and 8 ports just aren't enough. Its compact 10-inch form factor and cost-effective design make it the ideal solution for small and medium-sized offices, home networks, or rackmount environments where space and efficiency are key.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

With 16 Gigabit Ethernet ports and 2 SFP+ 10G uplink ports, you get all the connectivity you need without unnecessary bulk. With its versatile mounting options, the CSS318-16G-2S+ can be installed in 10-inch racks, standard 19-inch racks, or even side-by-side—fitting two switches in a single 1U 19-inch space.

Effortless Configuration with SwOS

Configuration is effortless with MikroTik's lightweight SwOS. Accessible directly from your web browser, SwOS gives you the core functionality of a managed switch and more:

Port-to-port forwarding

Broadcast storm control

MAC filtering

VLAN configuration

Traffic mirroring

Bandwidth limitation

Adjustment of MAC and IP header fields

Energy Efficient and Reliable

The CSS318 consumes just 10W without attachments and up to 13W under full load, keeping your network reliable while saving power.

Compact, Scalable, and Affordable

Compact, scalable, and simple to configure — the CSS318-16G-2S+IN is ready to enhance your network at an unbeatable price.

Summary: Mikrotik CSS318-16G-2S+IN. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16, Installed SFP+ modules quantity: 2. Rack mounting | Vendor Homepage:

https://mikrotik.com/product/css318_16g_2s_in#fndtn-specifications | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP+ modules quantity: 2 | 10G support: Yes | Rack mounting: Yes | Stackable: Yes | Product colour: White | Operating system installed: SwOS | Processor model: 98DX2518 | Flash memory: 16 | Mean time between failures (MTBF): 200000 | Power source: AC | AC input voltage: 100 - 240 | AC input frequency: 50/60 | Power consumption (max): 13 | Power over Ethernet (PoE): No | Operating temperature (T-T): -40 - 70 | Width: 218 | Depth: 157 | Height: 44 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Unit Calculated Weight: 1.53 | Product Net Weight: 1 | Unit Calculated Volume: 0.005022 | Units per Shipping Box: 10 | Unit Width: 24.5 | Shipping Box Height: 31 | Unit Depth: 28.5 | Unit Height: 6 | Name: NET SWITCH 16PORT 1000M 2SFP+/CSS318-16G-2S+IN MIKROTIK | Model: CSS318-16G-2S+IN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950