

Switch MIKROTIK CSS610-8G-2S+IN Desktop/pedestal 8x10Base-T 100Base-TX 1000Base-T 2xSFP+ CSS610-8G-2S+IN

Model: CSS610-8G-2S+IN

Manufacturer: MIKROTIK

EAN: 4752224006929

Product Code: 334117

R2,861

Eight 1G Ethernet ports and two SFP+ ports for 10G fiber connectivity. Portable, powerful and extremely cost-effective – this switch is an instant classic!

Cloud Smart Switch 610-8G-2S+IN is our answer to the everlasting demand for more power in a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

small and simple package. It comes with the lightweight SwOS which is easy to configure from your web browser. It gives you all the basic functionality for a managed switch, and more: you can manage port-to-port forwarding, broadcast storm control, apply MAC filters, configure VLANs, mirror traffic, apply bandwidth limitation and even adjust some MAC and IP header fields.
Summary: Mikrotik CSS610-8G-2S+IN. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. DC input voltage: 12 - 57 V. Power over Ethernet (PoE) | Vendor Homepage: https://mikrotik.com/product/css610_8g_2s_in#fndtn-specifications | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 2 | 10G support: Yes | Product colour: White | LED indicators: Yes | International Protection (IP) code: IP20 | Operating system installed: SwitchOS Lite | Memory type: Flash | Internal memory: 0.64 | Mean time between failures (MTBF): 200000 | Power source: DC/PoE | DC input voltage: 12 - 57 | Power consumption (max): 11 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Operating temperature (T-T): -20 - 60 | Width: 200 | Depth: 167 | Height: 46 | Unit Calculated Weight: 1.02 | Product Net Weight: 0.85 | Unit Calculated Volume: 0.004586 | Units per Shipping Box: 10 | Unit Width: 20 | Units per Pallet: 0 | Shipping Box Height: 34 | Unit Depth: 31.5 | Unit Height: 6 | Name: NET SWITCH 8PORT 1000M 2SFP+/CSS610-8G-2S+IN MIKROTIK | Model name: CSS610-8G-2S+IN

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950