




Switch TELTONIKA TSW2000000B0 PoE ports 8 240 Watts TSW200

Model: TSW200

Manufacturer: TELTONIKA

EAN: 4779051840120

Product Code: 334219

R2,132

TSW200 is industrial unmanaged switch from Teltonika Networks.

TSW200 is equipped with 2 SFP ports for long-range Fiber-optic communication and 8 Gigabit Ethernet ports which support IEEE802.3af and IEEE802.3at Power-over-Ethernet standards.

Classified as power source equipment (PSE), it enables centralization of the power supply, providing up to 30 watts per port and reducing the effort for installing power. It has 10/100/1000 Mbps Ethernet ports to provide an economical high-bandwidth solution for your industrial Ethernet network.

This rugged unmanaged industrial switch is ideal for professional high bandwidth applications where

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

it is necessary to provide both: reliable data connection and power supply.

- POE+
- SFP
- ETHERNET
- DURABILITY
- MOUNTING (DIN rail)
- POWER BUDGET

Summary: Teltonika TSW200. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 2000 entries. Networking standards: IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u. DC input voltage: 7 - 57 V. Power over Ethernet (PoE). Wall mountable, Rack mounting | Vendor Homepage: <https://teltonika-networks.com/product/tsw200/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP module slots quantity: 2 | Auto MDI/MDI-X: Yes | Networking standards: IEEE 802.3/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3u | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2000 | Packet buffer memory: 0.128 | DIN rail mounting: Yes | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: LAN/PoE/Status | Product colour: Aluminium | Rack mounting: Yes | Wall mountable: Yes | DC input voltage: 7 - 57 | Power consumption (max): 106 | Power consumption (typical): 1.8 | Power source: DC | Power supply included: No | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) voltage: 57 | Total Power over Ethernet (PoE) budget: 240 | Operating temperature (T-T): -40 - 75 | Depth: 44.2 | Height: 132 | Weight: 456 | Width: 95.1 | Model: TSW200 | Model name: TSW200 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001737 | Unit Calculated Weight: 0.6