



PLANET IGS-10020PT network switch Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Blue, White

Model: IGS-10020PT

Manufacturer: PLANET

EAN: 4711213689550

Product Code: 375349

R10,828

Certification: FCC Part 15 Class A, CE | Console port: RJ-45 | Port mirroring: Yes | MAC address table: 8000 entries | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | LED indicators: Yes | Operating relative humidity (H-H): 5 - 95% | MIB support: RFC 1213 MIB-II, IF-MIB, MAU-MIB | Access Control List (ACL): Yes | Number of queues: 8 | Link

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

aggregation: Yes | Switch type: Managed | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Web-based management: Yes | Networking standards: IEEE 802.1ad | Security algorithms: 802.1x RADIUS | Store-and-forward: Yes | Product colour: White | Product colour: Blue | Power over Ethernet (PoE) ports quantity: 8 | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3ah | Housing material: Aluminium | Security algorithms: SSH | Operating temperature (T-T): -40 - 75 °C | Total Power over Ethernet (PoE) budget: 240 W | Networking standards: IEEE 802.3u | Power requirements: 48VDC | Depth: 107.3 mm | Height: 152 mm | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bz | Full duplex: Yes | Networking standards: IEEE 802.3af | Gigabit Ethernet (copper) ports quantity: 8 | Switch layer: L3 | Management protocols: SSH, SSL, SNMP, Telnet | 10G support: No | Wall mountable: Yes | Weight: 1.03 kg | Multicast support: N | Width: 76.8 mm | Rack mounting: No | Auto MDI/MDI-X: Yes | Power consumption (max): 255 W | Switching capacity: 26 Gbit/s | International Protection (IP) code: IP30 | Networking standards: IEEE 802.1w | Harmonized System (HS) code: 85176990 | Power over Ethernet (PoE): Yes | Fiber optic connector: MiniGBIC | Throughput: 14.8 Mpps | DIN rail mounting: Yes | Jumbo frames support: Yes | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS) support: Yes | Number of VLANs: 255 | SFP module slots quantity: 2 | VLAN support: Yes | Copper ethernet cabling technology: 100BASE-TX | Basic switching RJ-45 Ethernet ports quantity: 8 | Copper ethernet cabling technology: 1000BASE-T | Copper ethernet cabling technology: 10BASE-T | Flow control support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950