



TP-Link TL-SF1005D Managed Fast Ethernet (10/100) White



Model: TL-SF1005D

Manufacturer: TP-LINK

EAN: 6935364020064

Product Code: 375352

R746

Certification: FCC, RoHS | AC input frequency: 50 Hz | Input current: 0.6 A | LED indicators: Yes | AC input voltage: 220 V | Package weight: 190 g | Warnings: Do not open the case or try to repair it yourself. | Networking standards: IEEE 802.3x | Compliance certificates: Federal Communications Commission (FCC) | Web-based management: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Ethernet LAN data rates: 10,100 Mbit/s | Warnings: Ensure the unit is adequately ventilated during operation. | Package type: Box | Product colour: White | Networking standards: IEEE 802.3u | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Power source: DC | Sustainability compliance: Yes | Auto-negotiation: Yes | MAC address table: 1000 entries | Height: 22 mm | Cables included: AC | Auto MDI/MDI-X: Yes | Fanless: Yes | Storage relative humidity (H-H): 5 - 90% | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Heat dissipation: 6.38 BTU/h | Operating relative humidity (H-H): 10 - 90% | Power over Ethernet (PoE): No | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

consumption (typical): 1.87 W | Switch type: Managed | Power supply included: No | Width: 103.5 mm | Operating temperature (T-T): 0 - 40 °C | DC input voltage: 5 V | Power consumption (max): 1.87 W | Switching capacity: 1.6 Gbit/s | Power connector: DC-in jack | Full duplex: Yes | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-T | Basic switching RJ-45 Ethernet ports quantity: 5 | Fast Ethernet (copper) ports quantity: 5 | Package height: 85 mm | Depth: 70 mm | Store-and-forward: Yes | Package width: 91 mm | Rack mounting: No | Spanning tree protocol: Yes | Supported network protocols: CSMA/CD, TCP/IP | Flow control support: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Package depth: 108 mm | AC adapter included: Yes | User guide: Yes | 10G support: No

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950