



## TP-Link 8-Port Gigabit Desktop Network Switch



Model: TL-SG1008D

Manufacturer: TP-LINK

EAN: 6935364092313

Product Code: 375359

# R1,097

Certification: CE, FCC, RoHS | Power consumption (max): 3.53 W | Ethernet LAN data rates: 10,100,480,800,1000 Mbit/s | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power over Ethernet (PoE): No | Package weight: 300 g | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.3i | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Operating relative humidity (H-H): 10 - 90% | Package type: Box | Package width: 110 mm | AC input frequency: 50/60 Hz | AC adapter included: Yes | Product colour: Black | Input current: 0.6 A | AC input voltage: 100 - 240 V | Storage temperature (T-T): -40 - 70 °C | LED indicators: Yes | Width: 180 mm | Cables included: AC | Depth: 90 mm | Power consumption (typical): 4.63 W | Power source: DC | Package height: 85 mm | Jumbo frames: 15000 | Package depth: 185 mm | User guide: Yes | Power supply included: Yes | Jumbo frames support: Yes | Housing material: Plastic | Store-and-forward: Yes | Heat dissipation: 15.8 BTU/h | Switch type: Unmanaged | DC input voltage: 9 V | Rack mounting: No | Gigabit Ethernet (copper) ports quantity: 8 | Maximum cable length: 100 m | Basic switching RJ-45 Ethernet ports quantity: 8 | Auto MDI/MDI-X: Yes | Fanless: Yes | Copper ethernet cabling technology: 1000BASE-T | Copper ethernet cabling technology: 100BASE-TX | Stackable: No | Copper ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

cabling technology: 10BASE-T | Switching capacity: 16 Gbit/s | Power connector: DC-in jack | Harmonized System (HS) code: 85176990 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | MAC address table: 4000 entries | Height: 25.5 mm | Packet forwarding rate (10 Mbps): 1488000 pps | Full duplex: Yes | Packet buffer memory: 2 MB | Auto-negotiation: Yes | Packet forwarding rate (1 Gbps): 14880 pps | Cable types supported: Cat3 | Wall mountable: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Packet forwarding rate (100 Mbps): 148800 pps | 10G support: No | Flow control support: Yes | Cable types supported: Cat4 | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Sustainability compliance: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: Do not open the case or try to repair it yourself.

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](https://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950