

TP-Link 300Mbps Wireless N WiFi Router

TP-Link 300Mbps Wireless N WiFi Router



Model: TL-WR841N/PL

Manufacturer: TP-LINK

EAN: 6935364091170

Product Code: 375362

R917

Certification: CE, FCC, RoHS | VPN support: PPTP, L2TP, IPSec | Quick start guide: Yes | Stateful Packet Inspection (SPI): Yes | Product colour: Black | Output voltage: 9 V | Width: 174 mm | Firewall security: SPI | Weight: 700 g | WLAN data transfer rates supported: 54 | Port forwarding: Yes | Dynamic DNS (DDNS): Yes | Ethernet LAN interface type: Fast Ethernet | WLAN data transfer rates supported: 11 | Frequency band: 2.4 GHz | Depth: 119 mm | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Product colour: White | Rack mounting: No | DHCP client: Yes | DC-in jack: Yes | xDSL connection: No | WLAN data transfer rates supported: 300 | 3G: No | Port triggering: Yes | Ethernet LAN: Yes | Harmonized System (HS) code: 85176990 | LED indicators: Power, Status, WLAN | Input current: 0.6 A | DHCP server: Yes | Ethernet WAN: Yes | Transmit power: 20 dBmW | Detachable antenna(s): No | DSL WAN: No | Cabling technology: 10/100Base-T(X) | Power source type: DC | DMZ support: Yes | Package height: 86 mm | Wi-Fi standards: 802.11b | 4G: No | Reset button: Yes | Mac operating systems supported: MacOS | Security algorithms: 128-bit WEP | Ethernet LAN data rates: 100 | On/off switch: Yes | Windows operating systems supported: Windows XP Professional x64 | Windows operating systems supported: Windows Vista Enterprise x64 | Windows operating systems

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: Windows 2000 Professional | Full duplex: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | WLAN data transfer rate (max): 300 Mbit/s | Package weight: 520 g | Windows operating systems supported: Windows 7 Home Basic | Windows operating systems supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows XP Professional | Web-based management: Yes | MAC address filtering: Yes | Package depth: 202 mm | Wi-Fi standards: 802.11g | Mobile network connection: No | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 7 Professional | VPN Passthrough: Yes | Antenna design: External | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11b | Security algorithms: WPS | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 7 Enterprise | 3G/4G USB modem compatibility: No | DoS attack prevention: Yes | Security algorithms: WPA2-PSK | Package width: 288 mm | Windows operating systems supported: Windows Vista Home Premium x64 | Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) | Universal Plug and Play (UPnP): Yes | Antennas quantity: 2 | Windows operating systems supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows 98SE | USB port: No | Windows operating systems supported: Windows Vista Home Premium | Windows operating systems supported: Windows XP Home | Windows operating systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT | Wi-Fi band: Single-band (2.4 GHz) | Windows operating systems supported: Windows Vista Business | Windows operating systems supported: Windows Vista Ultimate | Windows operating systems supported: Windows 7 Ultimate x64 | Security algorithms: SSID | Wi-Fi standards: Wi-Fi 4 (802.11n) | Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems supported: Windows 7 Professional x64 | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.3u | Security algorithms: 152-bit WEP | Windows operating systems supported: Windows Vista Home Basic | AC adapter included: Yes | Filtering description: IP, MAC, URL | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Height: 28 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Filtering: Yes | Operating relative humidity (H-H): 10 - 90% | Memory card slot(s): No | Linux operating systems supported: Yes | Security algorithms: WPA | Firewall: Yes | SIM card slot: No | Windows operating systems supported: Windows 7 Home Premium | Windows operating systems supported: Windows 7 Starter | Product type: Tabletop router |

Ethernet LAN (RJ-45) ports: 4 | Operating temperature (T-T): 0 - 40 °C | Power consumption (typical):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

8 W | Output current: 0.6 A | Antenna gain level (max): 5 dBi

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950