



TP-Link 300Mbps Wireless N WiFi Router



Model: TL-WR841N/PL

Manufacturer: TP-LINK

EAN: 6935364091170

Product Code: 375362

R464

Certification: CE, FCC, RoHS | VPN support: PPTP, L2TP, IPSec | Filtering: Yes | Reset button: Yes |
Windows operating systems supported: Windows 7 Home Premium | Windows operating systems
supported: Windows 7 Starter | Windows operating systems supported: Windows Vista Enterprise
x64 | Windows operating systems supported: Windows 2000 Professional | Package weight: 520 g |
Windows operating systems supported: Windows 7 Home Basic | Windows operating systems
supported: Windows 7 Ultimate | Windows operating systems supported: Windows 2000 | Windows
operating systems supported: Windows Vista Business | Windows operating systems supported:
Windows Vista Ultimate | Windows operating systems supported: Windows Vista Home Premium x64
| Windows operating systems supported: Windows XP Home x64 | Cables included: LAN (RJ-45) |
Windows operating systems supported: Windows XP Professional x64 | Windows operating systems
supported: Windows 7 Home Basic x64 | Windows operating systems supported: Windows Vista
Home Premium | Windows operating systems supported: Windows XP Home | Windows operating
systems supported: Windows 7 Starter x64 | Windows operating systems supported: Windows NT |

Windows operating systems supported: Windows Vista Home Basic x64 | Windows operating systems

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: Windows 7 Professional x64 | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows 7 Home Premium x64 | Windows operating systems supported: Windows 7 Enterprise x64 | Windows operating systems supported: Windows Vista Home Basic | Windows operating systems supported: Windows 7 Ultimate x64 | Windows operating systems supported: Windows Vista Enterprise | Windows operating systems supported: Windows 7 Professional | WLAN data transfer rates supported: 300 Mbit/s | Quick start guide: Yes | Wi-Fi standards: 802.11g | 3G: No | Windows operating systems supported: Windows Vista Business x64 | Windows operating systems supported: Windows XP Professional | WLAN data transfer rates supported: 11 | WLAN data transfer rates supported: 54 | Antennas quantity: 2 | Cabling technology: 10/100Base-T(X) | Wi-Fi standards: 802.11b | Power source type: DC | Linux operating systems supported: Yes | Antenna gain level (max): 5 dBi | Package depth: 202 mm | Memory card slot(s): No | Operating relative humidity (H-H): 10 - 90% | Product colour: Black | Width: 174 mm | Harmonized System (HS) code: 85176990 | Rack mounting: No | On/off switch: Yes | Weight: 700 g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Ethernet LAN data rates: 100 Mbit/s | VPN Passthrough: Yes | Full duplex: Yes | Antenna design: External | Height: 28 mm | Windows operating systems supported: Windows Vista Ultimate x64 | Windows operating systems supported: Windows 7 Enterprise | USB port: No | DC-in jack: Yes | Ethernet LAN interface type: Fast Ethernet | Frequency band: 2.4 GHz | Package width: 288 mm | Product type: Tabletop router | Port triggering: Yes | DMZ support: Yes | Product colour: White | AC adapter included: Yes | Power consumption (typical): 8 W | DHCP client: Yes | 4G: No | LED indicators: Power, Status, WLAN | Input current: 0.6 A | Output current: 0.6 A | Ethernet LAN: Yes | SIM card slot: No | Firewall security: SPI | Dynamic DNS (DDNS): Yes | Mobile network connection: No | DHCP server: Yes | Output voltage: 9 V | Package height: 86 mm | Operating temperature (T-T): 0 - 40 °C | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Wi-Fi band: Single-band (2.4 GHz) | Stateful Packet Inspection (SPI): Yes | Detachable antenna(s): No | Depth: 119 mm | Firewall: Yes | Universal Plug and Play (UPnP): Yes | Port forwarding: Yes | Ethernet LAN (RJ-45) ports: 4 | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Mac operating systems supported: MacOS | DSL WAN: No | Ethernet LAN data rates: 10 | DoS attack prevention: Yes | Security algorithms: WPA2-PSK | Web-based management: Yes | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.3u | Security algorithms: 152-bit WEP | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA | Filtering description: IP, MAC, URL | Networking standards: IEEE 802.3 | WLAN data transfer rate (max): 300 Mbit/s | MAC address filtering: Yes | Transmit power: 20 dBmW | xDSL connection: No | 3G/4G USB modem compatibility: No | Ethernet WAN: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Networking standards: IEEE 802.11b | Security algorithms: WPS | Security algorithms: SSID

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950