CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-11-28 00:06



Ubiquiti U6+ wireless access point 2402 Mbit/s White Power over Ethernet (PoE)

Model: U6+

Manufacturer: UBIQUITI

EAN: 810084691090

Product Code: 375375

R3,190

Certification: IC | Compliance certificates: CE | Sustainability certificates: Federal Communications Commission (FCC) | Sustainability certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | 6 GHz: No | Antenna type: Internal | MIMO: Yes | Quality of Service (QoS) support: Yes | Ethernet LAN (RJ-45) ports: 1 | Antenna gain level (max): 5.4 dBi | LED indicators: Yes | 2.4 GHz: Yes | Operating temperature (T-T): -30 - 60 °C | Product colour: White | Networking standards: IEEE 802.11b | 5 GHz: Yes | Networking standards: IEEE 802.11a | Power over Ethernet (PoE): Yes | Reset button: Yes | Maximum data transfer rate: 2402 Mbit/s | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: WPA2-Enterprise | Security algorithms: WPA-Enterprise | Security algorithms: WPA-PSK | Mounting kit: Yes | Power consumption (max): 9 W | Weight: 338 g | Networking standards: IEEE 802.11ac |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Operating relative humidity (H-H): 5 - 95% | Transmitting power: 23 dBmW | Number of users: 300 user(s) | Maximum indoor range: 139.35 m | Warnings: Do not dismantle the appliance - internal components may be hazardous to the user's health and should only be handled by qualified personnel. | Warnings: Avoid contact with liquids - the unit is not waterproof. | Height: 33 mm | Warnings: Risk of electric shock – use caution during installation and use. | VLAN support: Yes | Placement: Ceiling | Width: 160 mm | Maximum data transfer rate (5 GHz): 2402 Mbit/s | Maximum data transfer rate (2.4 GHz): 573.5 Mbit/s | DC voltage range: 44 - 57 V | Number of products included: 1 pc(s) | Depth: 160 mm | Housing material: Aluminium, Polycarbonate (PC) | Internal RJ-45 ports quantity: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950