

PLANET DIN-Rail L2+/L3 Manageable Managed L2+ Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Aluminium, Blue

Model: IGS-10020HPT-U

Manufacturer: PLANET

EAN: 4711605287135

Product Code: 375815

R12,632

Certification: FCC Part 15 Class A, CE e-Mark | Storage temperature (T-T): -40 - 85 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): Yes | Operating relative humidity (H-H): 5 - 95% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bz | Networking standards: IEEE 802.3af | International Protection (IP) code: IP30 | Networking standards: IEEE 802.1ag | Networking standards: IEEE 802.1w | Reset button: Yes | Switch layer: L2+ | 10G support: No | Product colour: Blue | Product

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

colour: Aluminium | Flow control support: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | VLAN support: Yes | Switching capacity: 26 Gbit/s | Wall mountable: Yes | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Installed SFP modules quantity: 2 | Depth: 107 mm | Weight: 1.08 kg | MAC address table: 8000 entries | Auto-negotiation: Yes | Width: 76.8 mm | LED indicators: Yes | Switch type: Managed | Power consumption (typical): 250 W | DIN rail mounting: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Jumbo frames support: Yes | Store-and-forward: Yes | Web-based management: Yes | Operating temperature (T-T): -40 - 75 °C | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ah | Housing material: Aluminium | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Traffic classification: Yes | Height: 152 mm | Networking standards: IEEE 802.3u | Full duplex: Yes | Link aggregation: Yes | Half duplex: Yes | Throughput: 19.34 Mpps

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950