



ASUS 4G-AX56 wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) Black



Model: 4G-AX56

Manufacturer: ASUS

EAN: 4718017869225

Product Code: 376148

R3,324

VPN support: VPN Client L2PT VPN Client OVPN VPN Client PPTP VPN Server OVPN VPN Server PPTP |
NAT functionality: PPTP, L2TP, IPSec, RTSP, H.323, SIP Passthrough, PPPoE relay | DC-in jack: Yes |
Reset button: Yes | Product colour: Black | Network address translation (NAT): Yes | Wake-on-LAN
ready: Yes | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11g | Networking
standards: IEEE 802.11n | Networking standards: IEEE 802.11a | Built-in display: No | Wi-Fi
standards: 802.11b | Parental control: Yes | Weight: 753 g | 3G bands supported: 2100 MHz | Wi-Fi
band: Dual-band (2.4 GHz / 5 GHz) | 3G: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | USB port: No |
3G/4G USB modem compatibility: Yes | 3G bands supported: 1800 | Wi-Fi standards: 802.11a | Wi-Fi
standards: Wi-Fi 6 (802.11ax) | WLAN data transfer rate (second band): 11 Mbit/s | Quick start guide:
Yes | Wi-Fi standards: 802.11g | DSL WAN: No | 3G standards: UMTS | 3G bands supported: 850 | SIM
card slot: Yes | Antennas quantity: 4 | Power source type: DC | 4G bands supported: 700 | 4G bands

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

supported: 2300 | Internal memory: 512 MB | Wi-Fi standards: Wi-Fi 4 (802.11n) | Built-in FTP server: No | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | AC adapter included: Yes | 4G bands supported: 1800 | 4G bands supported: 2100 | 4G bands supported: 800 | Guest access: Yes | DMZ support: Yes | 4G: Yes | LED indicators: LAN, Power, WAN | Ethernet LAN (RJ-45) ports: 5 | 4G standard: LTE-FDD | SIM card type: NanoSIM | Firewall: Yes | SSID-based VLAN assignment: Yes | Port triggering: No | 5G: No | Product type: Tabletop router | 3G bands supported: 900 | Mobile network generation: 4G | On/off switch: Yes | Indication light: Yes | Ethernet LAN: Yes | WLAN data transfer rate (third band): 54 Mbit/s | Ethernet LAN interface type: Gigabit Ethernet | Dynamic DNS (DDNS): Yes | Warranty card: Yes | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | Flash memory: 128 MB | Port forwarding: Yes | 4G bands supported: 2600 MHz | 4G bands supported: 850 | 4G bands supported: 2500 | WLAN data transfer rate (first band): 54 Mbit/s | Ethernet WAN: Yes | Built-in processor: No | WAN connection type: RJ-45 | DHCP server: Yes | Harmonized System (HS) code: 85176990 | Security algorithms: IPSec | WPS push button: Yes | WLAN data transfer rate (max): 1201 Mbit/s | Security algorithms: SIPS | Housing material: Plastic | MU-MIMO technology: Yes | Bandwidth control: Yes | Antenna design: Internal & external | Warnings: The product may emit radio waves that may interfere with other electronic devices. | Warnings: Avoid contact with liquids as this may cause electric shock. | Warnings: Do not open the appliance housing - risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950