

Ubiquiti U7 Lite 4300 Mbit/s White Power over Ethernet (PoE)

Ubiquiti U7 Lite 4300 Mbit/s White Power over Ethernet (PoE)



Model: U7-Lite

Manufacturer: UBIQUITI

EAN: 810084698747

Product Code: 376188

R2,895

Band steering: Yes | Rate limiting: Yes | Fast roaming: Yes | DC voltage range: 44 - 57 V | Fit AP mode features: Hotspot 2.0 | 6 GHz: No | Access point management: Wi-Fi schedule | Maximum Tx power (2.4 GHz): 23 dBmW | Maximum Tx power (5 GHz): 24 dBmW | Export Control Classification Number (ECCN): EAR99 | Wireless meshing: Yes | Coverage area: 115 m² | Spatial streams: 4 | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Networking standards: IEEE 802.11ac | Maximum data transfer rate: 4300 Mbit/s | Networking standards: IEEE 802.11ax | Networking standards: IEEE 802.11be | Networking standards: IEEE 802.11r | Frequency band: 2.4 - 5 GHz | 5 GHz: Yes | Networking standards: IEEE 802.11k | LED indicators: System | Networking standards: IEEE 802.11v | Ethernet LAN data rates: 1000 Mbit/s | MIMO: Yes | Product colour: White | Weight: 313 g | Networking standards: IEEE 802.11n | Security algorithms: PPSK | Ethernet LAN data rates: 2500 Mbit/s | 2.4 GHz: Yes | Reset button: Yes | Antenna type: Internal | Width: 171.5 mm | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

consumption (max): 13 W | Antennas quantity: 4 | Operating relative humidity (H-H): 5 - 95% |
Number of users: 200 user(s) | Power over Ethernet (PoE): Yes | Operating temperature (T-T): -30 -
40 °C | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Placement: Ceiling, Wall | Quantity per
pack: 1 pc(s) | Maximum data transfer rate (5 GHz): 4300 Mbit/s | Ethernet LAN (RJ-45) ports: 1 |
Housing material: Polycarbonate (PC) | Mounting kit: Yes | VLAN support: Yes | Height: 171.5 mm |
MIMO type: Multi User MIMO | Depth: 33 mm | Antenna gain level (max): 5 dBi

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950