



Asus Rack Platform (1U) AMD RS700A- E13-RS4U

Model: 90SF0451-M000N0

Manufacturer: ASUS

EAN: 4711636233217

Product Code: 376228

R97,127

Certification: BSMI, CE, CB, RCM, FCC(Class A), ISED | PCI Express x16 (Gen 5.x) slots: 2 | Number of main power supplies: 2 | Number of processors supported: 2 | Processor socket: Socket SP5 | Storage drive sizes supported: 3.5" | Height: 43.2 mm | Storage drive sizes supported: 2.5 | 80 PLUS certification: 80 PLUS Titanium | Chassis type: Rack (1U) | Hot-swap HDD bays: Yes | Supported DIMM module capacities: 32GB | Supported DIMM module capacities: 128GB | Depth: 483 mm | Power supply: 2000 W | Trusted Platform Module (TPM) version: 2.0 | Number of DIMM slots: 24 | Mini DisplayPorts quantity: 1 | Integrated BMC with IPMI: Yes | Number of fans: 8 fan(s) | Ethernet LAN: Yes | Width: 821.7 mm | Maximum RDIMM memory: 3.07 TB | Supported DIMM module capacities: 64GB | Supported memory types: DDR5-SDRAM | Supported DIMM module capacities: 96GB | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Storage temperature (T-T): -40 - 60 °C | Number of storage drives supported: 4 | Number of 3.5" bays: 4 | Storage relative humidity (H-H): 20 - 90% | Number of 2.5"/3.5" bays : 4 | Supported processors: AMD EPYC 9005 | Number of OCP3.0 ports: 2 | On-board graphics card memory: 64 MB | Weight: 13.8 kg | Supported RDIMM clock speeds: 5600 | Supported RDIMM clock speeds: 6400 MHz | Ethernet LAN (RJ-45) ports: 1 | Supported storage drive

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

types: HDD & SSD | Package weight: 16.7 kg | On-board graphics card model: Aspeed AST2600 |
Input current: 12A / 10A | Operating temperature (T-T): 10 - 35 °C | AC input frequency: 50/60 Hz |
Trusted Platform Module (TPM): Yes | AC input voltage: 100 - 127/220 - 240 V | LED indicators: Yes |
PCI Express slots version: 5.0

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950