



HP Series 7 Pro 24 inch WUXGA USB-C Monitor - 724pu



Model: 8Y2F7AA

Manufacturer: HEWLETT-PACKARD

EAN: 197498467719

Product Code: 376724

R5,939

Bundled software: HP Display Center HP Client Management Script Library | Box contents: Monitor DisplayPort™ cable HDMI cable VESA Mount adapter Warranty card Quick Setup Poster 1 USB Type-C to Type-C cable AC power cord Color calibration report | Certification: Australian-New Zealand MEPS BIS BSMI CB CCC CE CECP CEL cTUVus EAC FCC GS Mark ISO 9241-307 KC KCC NOM PSB SEPA TUV-S VCCI Vietnam MEPS WEEE ISC Low blue light WW application UAE Ukraine EE Microsoft WHQL Certification (Windows 11 and Windows 10) Ukraine CoC Ukraine DOC | Manufacturer warranty: HP three-year limited warranty | Tilt angle range: -5 - 20° | Display brightness (typical): 350 cd/m² | Height (with stand): 521.4 mm | HDCP: Yes | DisplayPort version: 1.4 | Product colour: Black | Power consumption (off): 0.3 W | Display diagonal: 61 cm (24") | Depth (with stand): 195 mm | HD type: WUXGA | Display resolution: 1920 x 1200 pixels | AC input frequency: 50/60 Hz | LED backlight: Yes | Aspect ratio: 16:10 | AC input voltage: 100 - 240 V | Response time: 5 ms | Width (with stand): 531.7 mm | Native aspect ratio: 16:10 | Display surface: Matt | DisplayPorts quantity: 1 | Cable lock slot: Yes | Energy efficiency class (SDR): E | USB upstream port type: USB Type-A | Picture-in-Picture: Yes | Screen shape: Flat | Haze rate: 25% | Feet colour: Black | Display bezel technology: Micro-Edge |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Built-in speaker(s): No | AMD FreeSync: No | USB Power Delivery (USB PD): Yes | Depth (without stand): 38.5 mm | Energy efficiency class (HDR): Not available | Flicker-free technology: Yes | USB Type-C downstream ports quantity: 1 | Pivot angle: 0 - 90° | Surface hardness: 3H | HP segment: Business | Response time measurement type: GTG (Gray to Gray) | Pixel density: 94 ppi | Built-in camera: No | Swivel angle range: -45 - 45° | Pivot: Yes | Stand included: Yes | USB Type-C DisplayPort Alternate Mode: Yes | General Product Safety Regulation (GPSR) URL: https://kaas.hpcloud.hp.com/pdf-public/pdf_11069394_en-US-1.pdf | Display diagonal (metric): 61 cm | Height (without stand): 342.9 mm | USB Power Delivery up to: 100 W | Anti-glare screen: Yes | Carbon emissions, logistics (kg of CO2e): 5 | USB upstream port type: USB Type-B | Number of USB Type-B upstream ports quantity: 1 | Energy consumption (SDR) per 1000 hours: 19.2 kWh | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | Display technology: LCD | Width (without stand): 531.7 mm | Weight: 5.2 kg | Viewable size, horizontal: 51.8 cm | Quick start guide: Yes | sRGB coverage (typical): 99% | HDMI: Yes | Display number of colours: 16.7 million colours | Compliance certificates: GS mark | Panel type: IPS | Display brightness: 350 cd/m² | Supported graphics resolutions: 1600 x 900 | Colour depth: 8 bit | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Power consumption (typical): 26.4 W | Built-in USB hub: Yes | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Colour gamut: 99% | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | European Product Registry for Energy Labelling (EPREL) code: 1887611 | Supported graphics resolutions: 1280 x 1024 (SXGA) | Contrast ratio (typical): 1500:1 | USB Type-A downstream ports quantity: 4 | Supported graphics resolutions: 720 x 400 | Compliance certificates: CECP | Compliance certificates: BIS | Vertical scan range: 50 - 100 Hz | Compliance certificates: CE | Power supply type: Internal | Low Blue Light technology: Yes | Fast charging: Yes | Compliance certificates: BSMI | Compliance certificates: CCC | Pixel pitch: 0.27 x 0.27 mm | Carbon emissions, manufacturing (kg of CO2e): 91 | Compliance certificates: Federal Communications Commission (FCC) | Storage relative humidity (H-H): 20 - 80% | Contrast ratio (dynamic): 10000000:1 | Feet colour: Silver | Tilt adjustment: Yes | Sustainability certificates: EPEAT | Viewing angle, vertical: 178° | Ethernet LAN: Yes | Swivelling: Yes | Viewable size, vertical: 32.4 cm | Operating temperature (T-T): 5 - 35 °C | Touchscreen: No | HDMI version: 2.0 | Ethernet LAN (RJ-45) ports: 1 | VESA Adaptive Sync support: Yes | Energy efficiency scale: A to G | Operating relative humidity (H-H): 5 - 95% | Maximum refresh rate: 100 Hz | Supported graphics resolutions: 1280 x 800 | Display brightness (peak): 350 cd/m² | Package width: 625 mm | Depth: 38.5 mm | HP GTIN (EAN/UPC): 193905205448, 193905205455, 193905205462, 193905418831, 193905205479, 193905205486 | Warranty card: Yes | Package weight: 7.8 kg |

Cables included: DisplayPort | Sustainability certificates: ENERGY STAR | Sustainability certificates:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

TCO | Weight (with stand): 5.2 kg | Total carbon footprint (kg of CO2e): 5.2 | Power consumption (max): 160 W | Power consumption (standby): 0.5 W | Supported graphics resolutions: 1024 x 768 (XGA) | Compliance certificates: CB | Compliance certificates: EAC | Cables included: HDMI | Cables included: AC | Detachable stand: Yes | Cables included: USB Type-C to USB Type-C | Carbon emissions, end-of-life (kg of CO2e): 16 | Supported graphics resolutions: 1440 x 900 (WXGA+) | Height: 342.9 mm | Horizontal scan range: 30 - 75 kHz | On Screen Display (OSD): Yes | Colour gamut standard: DCI-P3 | VESA mounting: Yes | UNSPSC-code: 43211902 | Total carbon emissions, w/o use phase (kg of CO2e): 73 | Backlight type: Edge LED | Colour gamut standard: sRGB | HDMI ports quantity: 1 | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Market positioning: Business | Remotely operated: Yes | Viewing angle, horizontal: 178° | Package type: Box | Height adjustment: Yes | Warnings: Unplug the monitor from the power source before cleaning. | NVIDIA G-SYNC: No | Width: 531.7 mm | Package height: 415 mm | Package depth: 142 mm | Colour gamut standard: Rec. 709 | Panel mounting interface: 100 x 100 mm | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Adjustable height (max): 15 cm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950