



Mercusys MB118-4G wireless router Fast Ethernet Single-band (2.4 GHz) White

Model: MB118-4G

Manufacturer: MERCUSYS

EAN: 6957939002848

Product Code: 376848

R1,245

Ethernet LAN interface type: Fast Ethernet | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN data rates: 10 | Width: 97.2 mm | Network address translation (NAT): Yes | Ethernet WAN: Yes | Reset button: Yes | Ethernet LAN data rates: 100 Mbit/s | Filtering: Yes | Power over Ethernet (PoE): Yes | Number of products included: 1 pc(s) | DC-in jack: Yes | Cables included: LAN (RJ-45) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Operating temperature (T-T): -30 - 60 °C | DHCP client: Yes | Antennas quantity: 4 | LED indicators: LAN, Power, WLAN | Mounting kit: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Cabling technology: 10/100Base-T(X) | Package type: Box | Ethernet LAN (RJ-45) ports: 1 | Quick installation guide: Yes | Storage temperature (T-T): -40 - 70 °C | Product colour: White | AC adapter included: Yes | DHCP server: Yes | Ethernet LAN: Yes | Depth: 54.7 mm | International Protection (IP) code: IP65 | Height: 230.9 mm | Product type: Portable router | USB port: No | Power source type: DC, PoE | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Security algorithms: WPA-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

PSK | Storage relative humidity (H-H): 5 - 90% | Wi-Fi band: Single-band (2.4 GHz) | Networking standards: IEEE 802.3af | Security algorithms: WPA2-PSK | WLAN data transfer rate (max): 300 Mbit/s | Networking standards: IEEE 802.3at | Web-based management: Yes | Compliance certificates: RoHS | Compliance certificates: CE | PoE injector included: Yes | 3G standards: UMTS | 3G bands supported: 850 | SIM card type: NanoSIM | 4G bands supported: 700 | Wall mountable: Yes | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 900 | 3G standards: HSPA+ | 4G bands supported: 2100 | 4G bands supported: 800 | 3G bands supported: 900 MHz | DSL WAN: No | WAN connection type: RJ-45 | 3G bands supported: 2100 | SIM card slot: Yes | Number of simultaneously connected devices (max): 32 | Antenna included: Yes | 4G bands supported: 1800 | Parental control: Yes | Detachable antenna(s): Yes | Antenna design: Internal & external | Mobile network generation: 4G | 3G/4G USB modem compatibility: No | 4G standard: LTE-TDD & LTE-FDD | Universal Plug and Play (UPnP): Yes | Firewall: Yes | Port triggering: Yes | 4G LTE category: 4 | Dynamic DNS (DDNS): Yes | DMZ support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950