



TP-LINK TL-MR6400 wireless router Single-band (2.4 GHz) Fast Ethernet 3G 4G Black

Model: TL-MR6400

Manufacturer: TP-LINK

EAN: 1210002609272

Product Code: 377119

R2,279

Certification: CE, RoHS | Ethernet LAN interface type: Fast Ethernet | Web-based management: Yes | MAC address filtering: Yes | LED indicators: LAN, Power, WLAN | Security algorithms: WPA | Stateful Packet Inspection (SPI): Yes | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Security algorithms: 128-bit WEP | Networking standards: IEEE 802.3 | Package height: 70 mm | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Package weight: 600 g | WLAN data transfer rate (max): 300 Mbit/s | Quick start guide: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11b | Ethernet LAN (RJ-45) ports: 4 | DHCP client: Yes | Networking standards: IEEE 802.11b | Output voltage: 9 V | Power source type: DC | Top Wi-Fi standard: Wi-Fi 4 (802.11n) | Filtering: Yes | 4G: Yes | Mac compatibility:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | Package width: 307 mm | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | 3G: Yes | Antennas quantity: 2 | Mac operating systems supported: Yes | Windows operating systems supported: Yes | Cables included: LAN (RJ-45) | Reset button: Yes | Width: 202 mm | Package depth: 223 mm | Ethernet WAN: Yes | Product colour: Black | Quick installation guide: Yes | DC-in jack: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC adapter included: Yes | Operating temperature (T-T): 0 - 40 °C | Manual: Yes | Operating relative humidity (H-H): 10 - 90% | Firewall: Yes | Detachable antenna(s): Yes | Ethernet LAN: Yes | 3G standards: UMTS | 3G standards: HSPA+ | Wi-Fi band: Single-band (2.4 GHz) | 3G bands supported: 1900 | Supported network protocols: IPv4, IPv6 | Depth: 141 mm | SIM card slot: Yes | Cabling technology: 10/100Base-T(X) | On/off switch: Yes | 4G standard: LTE | IP address filtering: Yes | DHCP server: Yes | Antenna design: External | Harmonized System (HS) code: 85176990 | Product type: Tabletop router | Height: 33.6 mm | Mobile network generation: 4G | 3G/4G USB modem compatibility: No | Output current: 0.85 A | Memory card slot(s): No | Linux operating systems supported: Yes | 3G bands supported: 2100 | DMZ support: Yes | DSL WAN: No | Port forwarding: Yes | 4G bands supported: 1900 | WAN connection type: RJ-45 | 4G bands supported: 1800 | USB port: No | 4G bands supported: 2100 | 4G bands supported: 800 | DoS attack prevention: Yes | WPS push button: Yes | 4G bands supported: 900 | 4G bands supported: 2600 | Universal Plug and Play (UPnP): Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950