



TP-Link 5-Port Gigabit Easy Smart Switch



Model: TL-SG105E

Manufacturer: TP-LINK

EAN: 1210002616836

Product Code: 377206

R995

Certification: FCC, CE, RoHS | Storage relative humidity (H-H): 5 - 90% | Operating temperature (T-T): 0 - 40 °C | Power consumption (max): 2.82 W | Quick start guide: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3u | Web-based management: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | MAC address table: 8192 entries | AC input voltage: 220 V | Depth: 98 mm | Jumbo frames support: Yes | Copper ethernet cabling technology: 100BASE-TX | LED indicators: Yes | Harmonized System (HS) code: 85176990 | Input current: 0.6 A | Packet buffer memory: 1 MB | Cables included: AC | Auto MDI/MDI-X: Yes | Height: 25 mm | Power supply included: Yes | Basic switching RJ-45 Ethernet ports quantity: 5 | Copper ethernet cabling technology: 10BASE-T | Package type: Box | Operating relative humidity (H-H): 10 - 90% | AC input frequency: 50 Hz | VLAN support: Yes | Rack mounting: No | Power over Ethernet (PoE): No | IGMP snooping: Yes | Width: 100 mm | User guide: Yes | Number of VLANs: 32 | 10G support: No | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Copper ethernet cabling technology: 1000BASE-T | Product colour: Black | Link aggregation: Yes | Store-and-forward: Yes | Gigabit Ethernet (copper) ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

quantity: 5 | Jumbo frames: 16000 | DC input voltage: 5 V | Throughput: 7.4 Mpps | Switch layer: L2 | Heat dissipation: 9.62 BTU/h | Switch type: Managed | Rack mount kit: Yes | Port mirroring: Yes | Flow control support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950