



TP-Link 28-Port Gigabit Easy Smart Switch with 24-Port PoE+



Model: TL-SG1428PE

Manufacturer: TP-LINK

EAN: 1210002617123

Product Code: 377272

R5,623

Certification: CE, FCC, RoHS | Virtual LAN features: Tagged VLAN | Cable types supported: Cat5 | Cable types supported: Cat5e | Cable types supported: Cat6 | Cable types supported: Cat4 | Rack mount kit: Yes | Virtual LAN features: Port-based VLAN | Link aggregation: Yes | Cable types supported: Cat3 | Fiber ethernet cabling technology: 1000BASE-X | Forwarding rate: 41.7 Mpps | Number of queues: 4 | Gigabit Ethernet (copper) ports quantity: 26 | Jumbo frames: 10000 | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-TX | Switching capacity: 56 Gbit/s | Basic switching RJ-45 Ethernet ports quantity: 26 | 10G support: No | Power over Ethernet plus (PoE+) ports quantity: 24 | Switch layer: L2 | Number of VLANs: 32 | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Copper ethernet cabling technology: 1000BASE-T | Switch type: Managed | Multicast support: Yes | VLAN support: Yes | SFP module slots quantity: 2 | Flow

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

control support: Yes | Harmonized System (HS) code: 85176990 | Jumbo frames support: Yes | Broadcast storm control: Yes | Rate limiting: Yes | IGMP snooping: Yes | Store-and-forward: Yes | Power supply included: Yes | Cables included: AC | Power source: AC | Security algorithms: SNMP | Networking standards: IEEE 802.3af | Storage relative humidity (H-H): 5 - 90% | Package height: 100 mm | AC input voltage: 100 - 240 V | Number of fans: 2 fan(s) | Rack mounting: Yes | Width: 440 mm | Package weight: 2.29 kg | Height: 44 mm | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Web-based management: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Operating temperature (T-T): 0 - 50 °C | Power consumption (max): 1039.03 W | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 250 W | Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Operating relative humidity (H-H): 10 - 90% | Form factor: 1U | AC input frequency: 50 - 60 Hz | Package width: 336 mm | Auto MDI/MDI-X: Yes | Depth: 220 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | User guide: Yes | Package depth: 528 mm | Product colour: Black

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950