



TP-Link Archer MR202 wireless router Fast Ethernet Dual- band (2.4 GHz 5 GHz) 4G Black



Model: MR202

Manufacturer: TP-LINK

EAN: 8885020625745

Product Code: 377409

R2,091

Certification: CE, RoHS | Receiver sensitivity: 5 GHz: 11a 54M: -78 dBm 11ac VHT20: -92 dBm 11ac VHT20: -72 dBm 11ac VHT40: -90 dBm 11ac VHT40: -67 dBm 11ac VHT80: -87 dBm 11ac VHT80: -64 dBm 2,4 GHz: 11g 54M: -74 dBm 11n HT20: -91 dBm 11n HT20: -72 dBm 11n HT40: -88 dBm 11n HT40: -69 dBm | VPN support: PPTP VPN, OpenVPN | Product colour: Black | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.11ac | DHCP client: Yes | Networking standards: IEEE 802.11a | Web-based management: Yes | LED indicators: LAN, Power, WAN, WLAN | Reset button: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Ethernet LAN data rates: 100 | DC-in jack: Yes | Ethernet LAN data rates: 10 | Stateful Packet Inspection (SPI): Yes | Power source type: DC | Port triggering: Yes | Port forwarding: Yes | Mac operating systems supported: Yes | DSL WAN: No | UMTS bands supported: 900 | Operating relative humidity (H-H): 10 - 90% | Ethernet LAN (RJ-45) ports: 3 | Operating temperature (T-T): 0 - 40 °C | Security algorithms:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

WPA | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | DMZ support: Yes | 4G bands supported: 700 | 4G bands supported: 2300 | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Security algorithms: 64-bit WEP | Security algorithms: WPA2 | Browser supported: Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 | Security algorithms: 128-bit WEP | 3G standards: UMTS | WAN connection type: RJ-45 | Windows operating systems supported: Windows 8 | 4G standard: LTE-TDD & LTE-FDD | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Guest access: Yes | Quality of Service (QoS) support: Yes | 4G bands supported: 900 | WLAN data transfer rate (max): 733 Mbit/s | WLAN data transfer rate (second band): 433 Mbit/s | Plug and Play: Yes | 4G bands supported: 1800 | Wi-Fi standards: Wi-Fi 5 (802.11ac) | 4G: Yes | Output voltage: 12 V | Wi-Fi standards: 802.11b | Dynamic IP: Yes | Cabling technology: 10/100Base-T(X) | 4G bands supported: 2100 | 4G bands supported: 800 | Wi-Fi standards: 802.11g | DHCP server: Yes | Transmit power: 20dBm(2.4G) 23dBm(5G) | Windows operating systems supported: Windows 7 | Dynamic DNS (DDNS): Yes | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | Windows operating systems supported: Windows XP | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | Height: 33.5 mm | Antenna design: External | Windows operating systems supported: Windows NT | WLAN data transfer rate (first band): 300 Mbit/s | Windows operating systems supported: Windows 2000 | Output current: 1 A | 3G: Yes | Antennas quantity: 2 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11a | Number of Ethernet LAN/WAN ports: 1 | Product type: Tabletop router | Windows operating systems supported: Windows 10 | 3G/4G USB modem compatibility: No | USB port: No | Windows operating systems supported: Windows 98SE | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Ethernet LAN interface type: Fast Ethernet | 3G standards: HSPA | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | UMTS bands supported: 850 | DoS attack prevention: Yes | Firewall: Yes | Security algorithms: WPA2-PSK | Width: 174 mm | Warnings: Do not expose the device to water or moisture. | Point-to-point protocol over Ethernet (PPPoE): Yes | Linux operating systems supported: Yes | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | Memory card slot(s): No | Ethernet WAN: Yes | Firewall security: IP and MAC Address Binding | Quick installation guide: Yes | Cables included: LAN (RJ-45) | Universal Plug and Play (UPnP): Yes | Static IP: Yes | Supported network protocols: IPv4, IPv6 | SIM card slot: Yes | Ethernet LAN: Yes | Depth: 124.5 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950